LENNTECH

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Filtration Selection Guide

Choosing the Right Filter for Your Application

From design and development through pilot to full scale manufacturing

You get More with Millipore's choice of filtration solutions

The right choice in your filtration train will make a huge difference in yields, process economics and product viability. The right choice in your filtration partner can provide consistent product quality, reliable supply, easy scale-up, multiple product configurations and peace of mind. With 50 years experience in the biotech and pharmaceutical industry we understand your complex needs and processes. From design and development through clinical trial material, to pilot manufacturing and full-scale production, Millipore has the products, expertise and services to help you get to market faster with an economical filter train that will work for you today and tomorrow.

Using this Guide is as Easy as 1, 2, 3






Utilize **Understanding the Options** to review the essential requirements that any filtration solution should offer to be effective in that application.

Then review Millipore's product recommendations and the key characteristics of each filter that make it the ideal choice.



Refer to the *Filter Quick Reference Guide* for product details such as surface area, volume, formats for various flow rates, and catalogue details.

Use the information in the **Product Information Section** for details on filter formats and connections, our disposable offering and comprehensive range of Access[®] Services.



ge-Scale Processing	1001
	And and a state of the state of
(1)-1)	HENGINE .
Eller all	10040-011 (02749-021
-	
	diversity.
	air an

Filtration Selection Guide

Product Information

Millipore offers every membrane and media in a wide range of formats and configurations that can be used from lab-scale to full-scale manufacturing. It is important to understand how each format can fit best in your application. The details in this section will give you basic knowledge of your choices.

Application Guide

This tool is intended to give you an overview of key applications and the recommended Millipore filtration solutions. Understanding that every process stream is different, we recommend that scaling and optimization testing be conducted in-house or utilizing Millipore's Access Services team. Use this information as a starting point for development or optimization.

Buffer Preparation	14
Cell Culture Media Preparation	16
	20
Mammalian Cell Culture Clarification	25
Protein and Antibody Downstream Processing	28
	32
Plasma Fractionation	36
Vaccines	45
Mammalian Cell	45
Viral Vectors	48
Plasmid DNA	50
Conjugates	52
	54
Final Aseptic Filling (SVP)	60
Large Volume Parenterals (LVP)	62
	66
	68
Tank Venting and Air Filtration	70

No tool will replace the need to conduct process development and optimization experiments. The unique nature of every process stream combined with application and regulatory requirements play a part in determining the optimum filtration train. Use this filtration selection guide as a starting point for selecting and sizing the most appropriate Millipore filter. No specific performance is guaranteed. Visit our on-line catalogue at www.millipore.com for individual product specifications and complete ordering information. For personal guidance on understanding the wide variety of options available please consult your local applications specialist or technical service.

Filter Format Quick Reference Guide*

						OF	PTICAP® CAP	PSULES							
Media/ Membrane	OptiScale® Capsule	Millipak® Units	Opticap XL1 Capsule	XL2	XL3	XL4	Opticap XL5 Capsule	XL10	XLT10	Opticap XLT20 Capsule	XLT30	Optiseal® Cartridge	2-Inch Cartridge	4-Inch Cartridge	
	С	larif	r i c a t	r i o n	a n d	Pre	∍ filt	trati	o n						
Clarigard®			•				•	•					•		
Milligard®	•			•		•	•	•	•	•	•			•	
Polysep [™] II	•			•		•	•	•	•	•	•			•	
Polygard [®] CR			•				•	•					•		
Polygard DF													•		
Durapore [®] 0.45 µm	•4	•4		•4		•4	•4	•				•			
	F i	nal F	Filtr	ati (o n										
Durapore 0.1 µm	•	•		•		•	•	•	•	•	•	•			
Durapore 0.22 µm	•	•		•		•	•	•	•	•	•	•			
Multilayer Durapore	•							•	•	•	•				
Multimedia Durapore	•							•							
Charged Durapore												•			
Durapore CBR	•														
Millipore Express [®] SHC	•				•		•	•	•	•	•				
Millipore Express SHF	•				•		•	•	•	•	•				
Millipore Express SHR	•				•		•	•	•	•	•				
I SIL SIL		ral C	Clea	r a n c	е	-2									
		<u> </u>				•2		•	•	•	•				
Viresolve NFR	•1	<u> </u>				•2		•	•	•	•				
	Τα	nk V	enti	-	and ,	Air			o n						
Aervent®	•3	/		•		•	•	•							

¹ Viresolve membranes are sold in the smaller OptiScale-25 Device format. ² Availa

² Available in original Opticap Capsules.

Charged Depth Filters

U	the second se			
	Mini Capsule	Pod	10-Inch Opticap Capsule	Stacked Lenticular Disc Filters
Millistak®+ HC				
Grade A1HC	•	•	•	•
Grade B1HC	•	•	•	٠
Grade COHC	•	•	•	•
Grade DOHC	•	•	•	٠
Millistak+ DE	•	•5	•	•
Millistak+ CE	•	•5	•	•
Viresolve Prefilter	•6	•5	•	

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

> * These tables only includes items mentioned in this selection guide. Visit our on-line catalogue at www.millipore.com for details on other filtration products. See connections on page 6.

⁵ Coming in 2005 ⁶ Viresolve prefilter available in OptiScale-40 device format.

Sinch Onlong Onlong Min Onlon Onlon Onlon<	CAR	TRIDGES						GAN	MA-COMPATIBL	e or Sterile Op	TICAP XL OR XLT	CAPSULES	
Image: sector of the sector		5-Inch Cartridge	10-Inch Cartridge	20-Inch Cartridge	30-Inch Cartridge	40-Inch Cartridge	Opticap XL3 Capsule	Opticap XL4 Capsule	Opticap XL5 Capsule	Opticap XL10 Capsule	Opticap XLT10 Capsule	Opticap XLT20 Capsule	Opticap XLT30 Capsule
Image: sector of the sector													
Image: sector of the sector			•	•	•	•							
Image: state of the state			•	•	•	•							
Image: select			•	•	•	•							
Image: state stat			•	•	•	•							
Image			•	•	•	•							
Image: state of the state of		•	•	•	•	•							
Image: state of the state of													
Image: state of the state of													
Image: Image Image: I		•	•	•	•			•	•	•	•	•	•
Image: start in the start in		•	•	•	•	•		•	•	•	•	•	•
Image: start in the start in			•	•	•								
Image: start in the start in			•	•	•								
Image: state of the state			•	•	•								
Image: state in the state in			•	•	•	•							
Image: state in the state interval of the state in		•	•	•			•		•	•	•	•	•
Image: state in the state in		•	•	•	•	•	•		•	•	•	•	•
Image: state in the state in													
$\begin{array}{c c c c c c c c c c c c c c c c c c c $		•	•	•	•		•		•	•	•	•	•
$\begin{array}{c c c c c c c c c c c c c c c c c c c $													
			•	•	•								
Image: state of the state			•	•	•								
• • <td></td>													
		•	•	•	•	•							

³ Aervent membrane is sold in the larger Aervent-50 Capsule format.

⁴ Single-layer filters only.

TFF Device Guide

	Pellicon XL	Mini	Cassette	Maxi	2-stack	4-stack	10-stack	20-stack
Microfiltration (MF)								
Prostak [™] Modules					•	•	•	•
Pellicon [®] Cassettes	•	•	•	•				
Ultrafiltration (UF)								
Pellicon [®] Cassettes	•	•	٠	•				

See Understanding Your Filter Options for an explanation of each filter format and available connections.

Understanding Your Filter Options

From small-scale screening tools, disposable capsules and Pods, to cartridges, stacked disc filters and MF or UF cassettes, Millipore produces a wide range of device formats for use in process development, pilot and full-scale manufacturing. Filter formats vary depending on membrane/media type. See page 2 to match the filter membrane with its' available device formats. For complete product specifications please refer to the on-line catalogue at www.millipore.com/products.

Quality Built Right In

Millipore's approach to quality is driven by our high standards of excellence and those of our customers. Our goal: to exceed customer expectations and ensure a sustained ability to provide a predicable, reliable supply of high-caliber products developed and produced in best-of-class environments.

Millipore membranes and devices are designed, developed and manufactured in accordance with a quality management system approved by an accredited registering body to an ISO® 9000 quality systems standard. Filters are subject to an array of quality control release tests, shipped with a certificate of quality and supported by a validation guide for compliance with regulatory agencies. For traceability, identification and easy document control, each device is clearly marked and labeled.

Cartridge

Opticap XL Capsule Choosing the Proper Pleated Filter

Filtration media is available in a range of formats. The choice provides each user an opportunity to match the filtration solution to their needs and process scale. In making your decision, consideration should be given to batch size, validation effort, lead time, labor, sterilization philosophy, economics, interfaces with process equipment and facilities services. All of these play a role and should be evaluated.

Single vs. Multi-layer Filters

When a process requires several filtration steps in series it is important to evaluate single vs. multi-layer options. Multiple stage single-layer filtration processes can be optimized by testing and adjusting each individual stage. This approach results in the most economical process possible. To ensure an optimized process single-layer filtration will require more small-scale testing, hardware, labor and validation.

Multiple layer filters are commonly used to compress multiple stages of single-layer filtration into a single element. Using filters with multiple layers shortens development time, and requires less hardware, floorspace and labor while assuring a robust and economical process.

> Aervent-50 Filter

OptiScale Capsules

Table of Contents

Quality Built Right In	4
Choosing the Proper Pleated Filter	4
Charged Depth Filters	5
A Wide Choice of Connections	6
Tangential Flow Filtration	7

Cartridge Filters

Cartridge filters are commonly used for larger processes requiring more filtration area and/or lower unit operating cost. Cartridge filters are used in conjunction with stainless steel housings and can safely withstand multiple steam-in-place cycles. Millipore cartridge filters are robust, strong and reliable. A variety of connections (See pg. 6) are available to suit your application and housing needs.

OptiScale Small-scale Disposable Capsules

OptiScale Disposable Capsule filters provide a convenient small-volume option for process development, screening and scaling. OptiScale capsule filters offer 13.8 cm² of filtration area, are faster and easier to set-up and use than conventional 47 mm discs with holders, and are completely disposable.

OptiScale-25 Small Volume Disposable Capsule Filters

Exclusively for the Viresolve Family of Filters OptiScale-25 capsules with Viresolve NFR or NFP membranes are used in small volume applications where feedstock requirements are minimal. Providing an active filtration area of 3.5 cm², these small devices are useful as an evaluation tool for impurity studies, protein passage studies, membrane area determination and virus validation. OptiScale-25 disposable capsule filters are sold as Evaluation Kits, each kit including 9 capsules: 3 devices each, of 3 different membrane lots.

OptiScale-25

Capsule



1

Opticap XL and XLT Disposable Capsule Filters

Disposable capsule filters save you time and resources. They eliminate the need to sanitize between cycles and reduce the associated validation effort. Capsules are commonly used in processes where fast turnover between cycles is required and to minimize worker exposure to hazardous process fluids. Capsule filters, depending upon the materials of construction, are autoclavable or gamma-compatible. Capsule filters have the unique advantage of being able to be coupled with disposable biocontainers into process assemblies that can be irradiated prior to use, thus assuring sterility.

Opticap capsules are available in a wide range of sizes, filter medias and inlet/outlet connections (See pg. 6). They are proven performers in the industry. No matter what your application need Millipore has the right configuration.

Sterile Options

Millipore Express and Durapore sterilizinggrade membranes are offered in 2 capsule options. Gamma-compatible capsules are designed to be sterilized by gamma irradiation prior to use and disposed of after use. Sterile Opticap XL or XLT capsules are gamma irradiated by Millipore and delivered sterile to your facility. **Opticap XL** disposable capsule filters have a unique design to minimize hold-up volume and reduce production losses and are available in a range of sizes for easy scale-up.

Opticap XLT disposable T-line capsule filters are available with or without a pressure gauge port for ease in monitoring process conditions. The T-line design accommodates series or parallel filtration to match your application needs. A specially-designed stand enables quick and easy integration into your existing process.

Millipak Disposable Filter Units

Millipak sterilizing-grade units have a unique stacked filter design that allows minimal hold-up volume and no particle shedding, making Millipak filters ideally suited for high value-added applications such as sterile finish and fill. Millipak filters are available in a range of filtration areas from 100 cm² to 1,000 cm², and have adjustable upstream vents and drain valves with O-ring seal and several connections for easy process control (See pg. 6).

Sterile Options

Millipak Gamma Gold units are available gamma-compatible and can be easily sterilized by gamma irradiation prior to use and disposed of after use.

> Millistak+ Mini Capsule

Charged Depth Filters

The ultimate in charged depth technology, Millistak+ filters utilize unique membranes and high quality materials. Choose any Millistak+ media type; HC, DE, CE or A and be confident that it will perform in a reliable manner.

Millistak+ Mini Small-scale Disposable Capsules

Millistak+ Mini capsules offer 23 cm² of effective surface area and are ideally suited for process development, screening and small-scale trials.

Opticap Disposable Capsule Filters

Original Opticap capsule filters with Millistak+ medias are ideal for pilot-scale and small-scale manufacturing.

Stacked Lenticular Disc Filters

Ideal for large-scale processing, stacked depth filters are available in 12- and 16-inch diameters and various surface areas to accommodate a range of process volumes.

The Millistak+ Pod


This new patented modular disposable filter format was designed for greater flexibility and productivity. Each Pod consists of one, five or ten 0.1 m² filter cells in a self-contained disposable enclosure. The Pods are lightweight and modular, and do not require housings. Multiple Pods can be configured up to 30 m² to match process volumes.

Pod

Opticap XLT Capsule

> Opticap XL Capsule

> > Stacked Disc Filte



* Inlet and outlet connections can be configured to meet your needs. Some connections are size and media/membrane dependant. Contact Millipore for details.

Tangential Flow Filtration

Millipore offers a variety of scalable microfiltration (MF) and ultrafiltration (UF) devices that utilize our patented highquality, void-free membranes offering you greater reliability, consistency and performance.

The Pellicon Family of Devices

The Pellicon UF family of cassettes comes in a choice of feed channel screens. The A screen (tight screen) is optimized to operate Biomax[®] void-free membranes with maximum flux in low viscosity applications. C Screen (coarse screen) is optimized for PLC membranes with maximum flow and is ideal for low to intermediate viscosity applications. For concentration and diafiltration, the C Screen is optimized for use with Biomax 50 to 1,000 kD membranes. For viscous solutions or solutions with higher levels of suspended solids, V Screen is the ideal choice. Pellicon filters have a low minimum working volume — as low as 175 mL of retentate volume per square meter of membrane

area — permitting high concentration factors to be reached with low starting volumes and maximizing the recovery of small sample volumes. No matter what Pellicon device you use, they all operate with the same pressure drop, flow velocity and concentration profile for true, rapid and simple scale-up.

Pellicon XL 50

Pellicon XL 50 cassettes incorporate Millipore's superior membranes in a small area (50 cm²) device. These cassettes operate with the same pressure drop, flow velocity and concentration profile as the larger Pellicon cassettes.

Mini Cassettes

Mini filters (0.1 m²) and holders are designed for laboratory filtration of 1 L to 10 L volumes, and scale-up linearly to Pellicon cassettes.

Standard Cassettes

Cassettes (0.5 m²) are designed for pilot and small scale manufacturing of 5 L to 100 L and linearly scale to Pellicon Maxi cassettes.

Maxi Cassettes

Pellicon Maxi cassettes (2.5 m²) are used in large scale manufacturing.

Prostak Family of Devices

MF Modules

Designed for clarification applications, the Prostak MF module is a tangential flow stacked plate device with an open-channel configuration. These filters can be steamed and are available in 2-stack (0.17 m^2), 4-stack (0.33 m^2), 10-stack (0.84 m^2), and 20-stack (1.7 m^2) modules.

UF Modules


Designed for concentration and diafiltration applications that require broad solvent compatibility, Prostak UF modules are a tangential flow stacked plate device with screened channels. These filters are available in 4-stack (0.39 m²), 10-stack (0.93 m²), and 20-stack (1.9 m²) modules.

TFF Membrane Overview*

Name	Pore Sizes/NMWL	Materials	pH Range Continuous	Protein Binding
Durapore Series	0.1, 0.22, 0.45, 0.65 µm	Hydrophilic PVDF	2 – 10 at 25 °C	Very low
Biomax Series	5, 8, 10, 30, 50, 100, 300 500 and 1,000 kD	High flux hydrophilic polyethersulfone	1 – 14 at 25 °C	Low
Ultracel® PLC Series	5, 10, 30, 100, 300 and 1,000 kD	Composite regenerated cellulose	2 – 12 at 25 °C	Very low

* This table includes only products mentioned in this selection guide.

Visit our on-line catalogue at www.millipore.com for details on other available TFF membranes.



Turnkey Solutions to Optimize Processing

Mobius Flexible Bioprocessing Solutions

We bring together unmatched expertise and disposable technologies to offer a complete, ready-to-process solution.

- Innovative separation and purification technologies
- The right connectology to link various steps in the process
- Quality container systems
- Custom design services
- Validation services and support



No matter what your application, step or scale, Millipore's Mobius solutions can revolutionize your process.

Turnkey disposable Mobius solutions can replace traditional stainless steel operations. Comprised of a suite of modular technologies and services that can be integrated into a ready-to-process solution, Mobius brings all the pieces together into a complete, validated system for your specific application needs.

Mobius solutions can offer:

- Reduced validation and cleaning efforts
- Quick turnaround times
- Flexibility in multi-product facilities
- Superior control over process consistency and security
- Reduced capital requirements

Millipore's Mobius technologies offer increased flexibility and easily integrate into existing processes, whether plastic-to-plastic or plastic-to-stainless.

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Filtration Devices

Millipore's high quality membrane filters are available in a wide range of self-contained, disposable configurations that don't require a stainless steel housing. Gamma-compatible and sterile options are available and are ideal for value-added applications. From small scale devices like Millipak filters to large volume Opticap XLT capsules, Millipore has a variety of filter technologies that are part of the suite of Mobius solutions.

For details on many disposable filter formats and inlet/outlet choices, see the Quick Reference Guide on page 2 and Understanding Your Filter Options beginning on page 4.

Container Systems


Millipore offers HyClone HyQ[®] CX5-14 and CX3-9 BioProcess Container[™] (BPC[®]) systems as a part of integrated Mobius assembly solutions. A wide range of flexible, scalable containers are available from small volume 2-D configurations starting at 50 mL to large volume 3-D configurations up to 1,500 L.

Two-dimensional Systems*	Applications	Size
2-D Small Volume End-Ported Hanging Pillow	Process development, QC sampling, bulk product storage, transfer and collection	50, 100, 250, 500 mL; 1, 2 L
2-D Small Volume Face-Ported	Process development, QC sampling, bulk product storage, transfer and collection	200, 500 mL; 1, 2 L
2-D Hanging/Freezing	Applications requiring freezing/thaw- ing, heat inactivation and irradiation of product	5, 10, 20 L
2-D Large Volume Face-Ported	Formulation and filling of sterile media, buffers and other process liquids; bioreactor and fermentation feed and harvest; waste collection; transportation and storage of bulk intermediate and final product	5, 10, 20, 50, 100, 200, 300 L
Three-dimensional Systems*	Applications	Size
3-D Rectangular	Formulation and filling of sterile media, buffers and other process liquids; bioreactor and fermentation feed and harvest; waste collection; transportation and storage of bulk intermediate product	50, 100, 200, 500, 900, 1,000, 1,500 L
Tank Liner	Media hydration, non-sterile mixing, refiltration of process intermediates	50, 100, 200, 300, 500, 1,000, 1,500 L
Mixtainer [™] Mixing System	Stirring, suspending, holding and storing sterile fluids	50, 100, 200 L

* Bioprocessing containers are only available as an integrated part of Mobius assemblies. Containers are not sold individually. Other container systems, configurations and accessories are available. Contact your Millipore Application Specialist.

Connectology

Disposable Lynx[®] connectors, clamps and valves provide the critical link between disposable fluid paths and the various steps in your process. The easy to use and







Product	Туре	Size	Cat No.
Lynx ST	Steam To	$^{3\!\!\!/}_{2\!\!\!/}$ in. TC x $^{\prime\!\!\!/}_{2\!\!\!/}$ in. hose barb 1 $^{\prime\!\!\!/}_{2\!\!\!/}$ in. TC x $^{\prime\!\!\!/}_{2\!\!\!/}$ in. hose barb	STC11FHN01 STC2T12N01
Lynx S2S	Sterile To Sterile	$^{1}\!/_{\!2}$ in. x $^{1}\!/_{\!2}$ in. hose barb	SSCSHB2N01
Lynx Non-Metal Clamp		½ in. – ¾ in. TC 1 in. – 1½ in. TC	P83062 P83063
Other Connector Types Available	 Colder Products[®] Quick Connects BioQuate Connectors 		Only sold in integrated systems
Tubing and Manifolds	 C-Flex[®] Platinum-cured Silicone 		Only sold in integrated systems

Custom Design Services

Millipore is your one point of contact for the design, development and validation support of your Mobius assembly systems. Our partnerships with various container and

component vendors means you get the best combination of expertise and technology in a single, integrated solution to fit your application and specifications.



WERE SPECIFICATION DRANES


Mobius Flexible Solutions

Validation and Support Services

Validation and regulatory compliance are essential components of any process. Unlike any other partner, Millipore Access Services team (See pg. 12) can provide assistance on how to successfully integrate and validate innovative Mobius processes into your operations.

Innovative Mobius Assembly Systems

By combining Mobius flexible manufacturing technologies – filters, connectors and valves, container systems, etc. – together with custom design services, validation services and support, Millipore offers turnkey solutions that can optimize your process. Many traditional stainless processes can be transformed with single-use, integrated and validated assemblies.



Proven Application, Validation and Engineering Support

ACCESS SERVICES



For over 50 years Millipore has been providing unmatched application, validation and engineering expertise to biotech and pharmaceutical companies around the globe. We understand the need for quality, cost containment and regulatory compliance at every stage from molecule to market.

Our philosophy is simple; be scientific, be practical, perform. We ask the right questions, practice excellent science, understand your application and the required validation, and provide defensible documentation. We let you concentrate on the success of your busines while the Access Team concentrates on the details.

Streamlining Compliance

Millipore has developed a range of regulatory and compliance services designed to meet the stringent data and documentation requirements of regulatory agencies.

- Microbial Retention Testing
- Drug Product Integrity Testing
- Extractable Analysis
- Drug Product Compatibility Analysis

Our process and validation expertise, coupled with our knowledge of world regulatory guidance, has enabled many drug manufacturers to successfully prove compliance while saving time and valuable resources.



ACCESS LAB solutions provide access to a team of professionals and state-of-the-art facilities. Our global team is ready to provide standard service packages or individually customized solutions to all your scaling, development, validation and testing needs.



ACCESS **ON-SITE** brings our expertise directly to you. Our field-based team provides a variety of services based on your needs. From on-site trials and testing to equipment validation, operator training, and system commissioning — if you need Millipore on-site we'll be there.

Process Development and Optimization

Whether at your site or in our lab, our comprehensive range of products, integrated technologies and support services will help solve your process development, optimization, validation and monitoring challenges.

- Design, Technology Selection, Sizing and Protocol Development
- Process Scaling, Optimization and Yield Improvements
- Validation and Engineering
- Process Monitoring, Quality Control and Technical Support

Comprehensive Training and Certification Programs

Millipore's Access Training program is recognized around the globe for its range of courses and quality content. From scale-up without compromise to advanced aseptic processing validation school, Millipore's training courses and seminars keep pace with the industry's changing needs. Millipore is certified by IACET and is authorized to grant continuing education credits. Documentation to satisfy GMP requirements is provided for certified training courses.

Advanced Process Design and Engineering

From process design reviews and software consulting to system commissioning and validation, our team supports the entire process.

- User Requirements Specification
- Functional Specification
- System Design and Construction
- $\bullet\,$ FAT, SAT, IQ/OQ and PQ Assistance
- SOP Development
- Operator Training and Certification

Visit www.millipore.com/accessservices today!



ACCESS **CONSULTING** offers guidance in a variety of areas. From development, scaling and optimization strategies to system and plant design and regulatory compliance Millipore experts partner with you to ensure success.




ACCESS **TRAINING** provides a broad range of training and certification courses to support the development and compliance needs of your personnel. Training includes lectures, workshops, hands-on exercises and case studies. Training is conducted in one of our worldwide training centers or at your facility.

Buffer Preparation

Buffer solutions are required for a number of purification steps and are critical to process efficiency and final product quality. Buffer filtration is critical to protect the life of chromatography columns, downstream UF steps and to ensure an endotoxin-free final product. Buffer solutions are typically filtered using sterilizing-grade membrane filters. Depending on the salt concentration and buffer properties, prefiltration may be needed.

For details on Tank Venting 2, see page 70.





Essential Process Requirements	Recommended Filter	Filter Characteristics
Sterile Filtration		
 Utilize a sterilizing-grade membrane to remove contaminants and ensure sterility Must work with a variety of process fluids across a range of pH levels Preserve product purity Able to withstand demanding steam-in-place requirements Depending on salt concentration and fluid properties, prefiltration may be needed 	 Single-layer Millipore Express SHF 0.2 μm Filters 	 Sterilizing-grade PES membrane providing broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site
indy be needed	Double-layer Millipore Express SHC 0.5 μm + 0.2 μm Filters	 Sterilizing-grade PES membrane with an additional PES prefilter layer all in one pleated device Double-layer construction provides excellent capacity even in high salt conditions >1M PES membrane provides broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric PES pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site
	ALTERNATIVE: If a PVDF membrane is r a proven performer for decades.	eeded, Millipore's Durapore Family of Filters have been

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
	13.8 cm ²	SGEPA47FF3
0.5 µm + 0.2 µm Membrane	13.8 cm ²	SHGEA47FF3

Recommended Filters

Volume	Filter Format	Area/Filter	Catalogue No.
0-400 L	Single-layer Millipore Express SHF Filters Opticap XL3 Capsule Opticap XL3 Gamma-compatible Capsule	0.16 m ² 0.17 m ²	KGEPA03TT3 KGEPG03TT3
400-800 L	Opticap XL5 Capsule	0.29 m ²	KGEPA05TT1
	Opticap XL5 Gamma-compatible Capsule	0.31 m ²	KGEPG05TT1
	5-inch Cartridge	0.29 m ²	CGEP75TP3
800-1,600 L	Opticap XL10 Capsule	0.54 m ²	KGEPA10TT1
	Opticap XL10 Capsule	0.54 m ²	KGEPA1TTT1
	Opticap XL10 Gamma-compatible Capsule	0.57 m ²	KGEPG10TT1
	Opticap XLT10 Gamma-compatible Capsule	0.57 m ²	KGEPG1TTT1
	10-inch Cartridge	0.54 m ²	CGEP71TP3
1,600-3,200 L	Opticap XLT20 Capsule	1.08 m ²	KGEPA2TTT1
	Opticap XLT20 Gamma-compatible Capsule	1.14 m ²	KGEPG2TTT1
	20-inch Cartridge	1.08 m ²	CGEP72TP3
3,200-4,800 L	Opticap XLT30 Capsule	1.62 m ²	KGEPA3TTT1
	Opticap XLT30 Gamma-compatible Capsule	1.71 m ²	KGEPG3TTT1
	30-inch Cartridge	1.62 m ²	CGEP73TP3
0-200 L	Double-layer Millipore Express SHC Filters Opticap XL3 Capsule Opticap XL3 Gamma-compatible Capsule	0.13 m ² 0.13 m ²	KHGEA03TT3 KHGEG03TT3
200-450 L	Opticap XL5 Capsule	0.23 m ²	KHGEA05TT1
	Opticap XL5 Gamma-compatible Capsule	0.24 m ²	KHGEG05TT1
	5-inch Cartridge	0.23 m ²	CHGE75TS3
450-1,000 L	Opticap XL10 Capsule	0.49 m ²	KHGEA10TT1
	Opticap XL10 Capsule	0.49 m ²	KHGEA1TTT1
	Opticap XL10 Gamma-compatible Capsule	0.54 m ²	KHGEG10TT1
	Opticap XLT10 Gamma-compatible Capsule	0.54 m ²	KHGEG1TTT1
	10-inch Cartridge	0.49 m ²	CHGE71TS3
1,000-2,000 L	Opticap XLT20 Capsule	0.98 m ²	KHGEA2TTT1
	Opticap XLT20 Gamma-compatible Capsule	1.09 m ²	KHGEG2TTT1
	20-inch Cartridge	0.98 m ²	CHGE72TS3
2,000-3,000 L	Opticap XLT30 Capsule	1.47 m ²	KHGEA3TTT1
	Opticap XLT30 Gamma-compatible Capsule	1.63 m ²	KHGEG3TTT1
	30-inch Cartridge	1.47 m ²	CHGE73TS3

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.


Cell Culture Media Preparation

The cells used to produce therapeutic proteins require a precise balance of nutrients to support their reproduction and growth. These nutrients are provided in the form of growth media, which must be sterile. For media containing animal derived components, final sterilizing-grade filtration should assure the removal of bacteria and mycoplasma. Media is typically mixed in bulk and then aseptically transferred to the bioreactor. Prefiltration is used to remove the bulk of particulate and colloidal contaminants from the media in order to extend the service life of the filter train. Prefilters must be sized appropriately to handle batch to batch media variability, as well as ensuring that the sterile media fill in the bioreactor is completed successfully and on time.

Filter Recommendations

Millipore's Express SHC and SHR filters are recommended for the scale-up and manufacture of tissue culture media for the production of MAbs, vaccines, and other biological therapeutics that require high throughput, flow rates and superior filtration economics.

For details on Tank Venting 4, see page 70.



 Triple-layer Millistak+ HC Filters (Grade A1HC) ALTERNATIVE: If media stream is less possible stream	 Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Unique design enables the compression of multiple process steps into one, lowering overall filtration costs <i>lugging, Millipore suggests testing single-layer Grade 75DE Millistak+ Filters in your</i> Designed for the protection of downstream 0.1 µm sterilizing-grade filters Triple layer construction ensures high particle loading and capacity Validated for multiple sanitization and SIP cycles Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Non-fiber releasing structure preserves product purity Cell growth studies confirm growth properties are preserved
(Grade W1, 1.0 µm + 0.2 µm + 0.1 µm) 3 Millipore Express SHC	 Triple layer construction ensures high particle loading and capacity Validated for multiple sanitization and SIP cycles Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Non-fiber releasing structure preserves product purity Cell growth studies confirm growth properties are preserved
	 Designed for media additives and prefiltered tissue culture media in batch sizes ranging from 100 to 20,000 L Asymmetric pore structure delivers superior flow rates and capacity over a range of CHO and NSO media PES membrane provides broad chemical compatibility across a wide pH range (1–14) 100% integrity tested to ensure quality Can be integrity tested on-site Robust construction validated for multiple SIP cycles
ALTERNATIVE: If a PVDF or low protein small-scale trials.	binding membrane is needed please include Durapore 0.22 µm Filters in your
Triple-layer Millistak+ HC Filters (Grade A1HC)	 Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Unique design enables the compression of multiple process steps into one, lowering overall filtration costs
ALTERNATIVE: If media stream is less plu	rgging, Millipore suggests testing Grade 75DE Millistak+ Filters in your small-scale trials.
2 Double-layer Polysep II Filters (Grade W3, 1.0 µm + 0.2 µm)	 Designed for the protection of downstream 0.22 µm sterilizing- grade filters Reliable prefilter for concentrated solutions across a full range of flow rates Robust construction ensures high particle loading and capacity Validated for multiple sanitization and SIP cycles Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Non-fiber releasing structure preserves product purity Cell growth studies confirm growth properties are preserved
	 Triple-layer Millistak+ HC Filters (Grade A1HC) ALTERNATIVE: If media stream is less plu Double-layer Polysep II Filters (Grade W3, 1.0 µm +



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.	Filter Format	Area/Filter	Catalogue No.
Bacterial and Mycoplasma			Bacterial		
OptiScale Capsules			OptiScale Capsules		
Single-layer Millipore Express SHR 0.1 µm mer	nbrane	SVEPA47FF3	Double-layer Millipore Express SHC		
Double-layer Millipore Express SHR			0.5 µm + 0.2 µm membrane		SHGEA47FF3
0.1 µm + prefilter layer	13.8 cm ²	SHVEA47FF3	Durapore 0.22 µm membrane	23 cm ²	SVGLA47FF3
Durapore 0.1 µm membrane		SVVLA47FF3	Double-layer Polysep II Grade W3 media		SGW3A47FF3
Triple-layer Polysep II Grade W1 media		SGW1A47FF3			
Millistak+ Mini Capsules			Millistak+ Mini Capsules		
Triple-layer Grade A1HC	23 cm ²	MA1HC23HH3	Triple-layer Grade A1HC	23 cm ²	MA1HC23HH3
Single-layer Grade 75DE	∠3 cm²	M75DE23HH3	Single-layer Grade 75DE	∠3 Cm²	M75DE23HH3

Recommended Filters

Recommended Thiers		Range	Range			Gamma-
Media/Membrane	Area/Filter	No Prefiltration Volume	With Prefiltration Volume	Cartridge	Standard Capsule	compatible Capsule
Bacterial and Mycoplasma Retention	n					
Millipore Express SHR Filters*						
Single-Layer (0.1 µm)	0.10 2	70	0501			
Opticap XL3 Capsule Opticap XL5 Capsule	0.12 m ²	70 L	250 L		KVEPA03TT3	KVEPG03TT3
or 5-inch Cartridge	0.22 m ²	1501	480	CVEP75TS3	KVEPA05TT1	KVEPG05TT1
Opticap XL10 Capsule	0.22 m	100 L	400 L	CVEI/ 0100	ICVEI/ COSTITI	
or 10-inch Cartridge	0.50 m ²	250 L	950 L	CVEP71TS3	KVEPA10TT1	KVEPG10TT1
Opticap XLT20 Capsule						
or 20-inch Cartridge	1.00 m ²	550 L	1,900 L	CVEP72TS3	KVEPA2TTT1	KVEPG2TTT1
Opticap XLT30 Capsule	1.50.0	0.50.1		0. (5570700		
or 30-inch Cartridge	1.50 m ²	850 L	2,800 L	CVEP73TS3	KVEPA3TTT1	KVEPG3TTT1
Double-Layer (0.1 µm + prefilter)						
Opticap XL3 Capsule	0.14 m ²	100 L	300 L		KHVEA03TT3	KHVEG03TT3
Opticap XL5 Capsule	0.07.0		(00)			
or 5-inch Cartridge	0.27 m ²	200 L	600 L	CHVE75TS3	KHVEA05TT1	KHVEG05TT1
Opticap XL10 Capsule or 10-inch Cartridge	0.53 m ²	4501	1.400 L	CHVE71TS3	KHVEA10TT1	KHVEG10TT1
Opticap XLT20 Capsule	0.00 m	4001	1,400 L	CHVE/ HOO	KINEATOTT	KINEOTOTT
or 20-inch Cartridge	1.07 m ²	950 L	2,800 L	CHVE72TS3	KHVEA2TTT1	KHVEG2TTT1
Opticap XLT30 Capsule						
or 30-inch Cartridge	1.60 m ²	1,400 L	4,200 L	CHVE73TS3	KHVEA3TTT1	KHVEG3TTT1
					Standard	
Media/Membrane	Area/Filter	Low Range	High Range	Cartridge	Capsule	
Triple-layer Polysep II						
Grade W1 (1.0 µm + 0.2 µm + 0.	.1 μm) Filters					
Opticap XL5 Capsule						
or 4-inch Cartridge	0.19 m ²	95 L	380 L	CGW1M4S03	KGW1A05TT1	-
Opticap XL10 Capsule or 10-inch Cartridge	0.46 m ²	230 L	920 L	CGW171S03	KGW1A10TT1	
6						
Media/Membrane	Area/Filter	Low Range	High Range	Stack	Capsule	Pod
Triple-layer Millistak+ HC Filters						
Grade A1HC						
1-cell Pod	0.1 m ²	100 L	300 L			MA1HC01FS
5-cell Pod	0.5 m ²	500 L	1,500 L			MA1HC05FS
Opticap Capsule, 10-inch	650 cm ²	65 L	195 L		KA1HC10FF1	
2-cell Stack, 16-inch 8-cell Stack, 16-inch	0.45 m ² 1.8 m ²	450 L 1,800 L	1,350 L 5.400 L	LA1HCH6S6 LA1HCG6S2		
10-cell Pod	1.8 m ² 1.0 m ²	1,800 L 1,000 L	3,000 L	LATHCG03Z		MA1HC10FS
ro centou	1.0 11-	1,000 L	5,000 L			MATHCI UF3

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Media/Membrane	Area/Filter	Range No Prefiltration Volume	Range With Prefiltration Volume	Cartridge	Standard Capsule	Gamma- compatible Capsule
Bacterial Retention Only						
Double-layer Millipore Express SH	C (0.5 µm + 0.2 µm)	Filters				
Opticap XL3 Capsule Opticap XL5 Capsule	0.13 m ²	230 L	650 L		KHGEA03TT3	KHGEG03TT3
or 5-inch Cartridge Opticap XL10 Capsule	0.23 m^2	440 L	1,230 L	CHGE75TS3	KHGEA05TT1	KHGEG05TT1
or 10-inch Cartridge Opticap XIT20 Capsule	0.49 m ²	1,000 L	2,800 L	CHGE71TS3	KHGEA10TT1	KHGEG10TT1
or 20-inch Cartridge Opticap XIT30 Capsule	0.98 m^2	2,000 L	5,600 L	CHGE72TS3	KHGEA2TTT1	KHGEG2TTT1
or 30-inch Cartridge	1.47 m ²	3,000 L	8,300 L	CHGE73TS3	KHGEA3TTT1	KHGEG3TTT1
Media/Membrane	Area/Filter	Low Range	High Range	Cartridge	Standard Capsule	
Double-layer Polysep II Grade W3 (1.0 µm + 0.2 µm) Fil Opticap XL5 Capsule	Iters					
or 4-inch Cartridge Opticap XL10 Capsule	0.19 m ²	95 L	380 L	CGW3M4S03	KGW3A05TT1	-
or 10-inch Cartridge	0.46 m ²	230 L	920 L	CGW371S03	KGW3A10TT1	-
Media/Membrane	Area/Filter	Low Range	High Range	Stack	Standard Capsule	Pod
Triple-layer Millistak+ HC Filters Grade A1HC						
1-cell Pod	0.1 m ²	100 L	300 L	-	-	MA1CH01FS1
5-cell Pod	0.5 m ²	500 L	1,500 L	-	-	MA1HC05FS1
Opticap Capsule	650 cm ²	65 L	195 L	-	KA1HC10FF1	-
2-cell Stack, 16-inch	0.45 m ²	450 L	1,350 L	LA1HCH6S6	-	-
8-cell Stack, 16-inch	1.8 m ²	1,800 L	5,400 L	LA1HCG6S2	-	-
10-cell Pod	1.0 m ²	1,000 L	3,000 L	-	-	MA1HC10FS1

*Millipore Express SHR Filters are in final development. Specifications may change. Consult technical services for details.

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.


Microbial Cell Culture Clarification

Microbial fermentation is used to produce products such as therapeutic proteins, antibiotics, hormones, enzymes, amino acids, blood substitutes and alcohol. The product of interest may be expressed by microbial cells or be intracellular (cytoplasmic or periplasmic in the case of bacterial cells).

To obtain the desired product, it must first be separated from the cells and other debris in the fermentation broth. In the case of intracellular products, the cells must be lysed and the lysate must be clarified to remove the cell debris and other contaminants. Depending on the process, additional clarification steps may be needed. Filtration is also used to process fermentation additives such as nutrients and pH adjusters prior to addition into the fermenter.

Due to the variability in the expression system characteristics such as percent solids, starting turbidity, particle size distribution and more between various microbial strains, no specific sizing recommendations are provided in this guide. Please contact your local applications specialist for details regarding your application.


For details on Tank Venting 4, see page 70.



Inclusion Body (IB) Purification Vent **IB** Solubilization Fermentation Harvest Cell Lysis Lysate Bioburden Clarification Reduction

Protein Refold Pool Clarification






Fermentation

Cell Lysis Harvest

Lysate Clarification

Bioburden Reduction

Where Can Recombinant Proteins Be Located?



- 1. Secreted into the media
- 2. Cytoplasm: soluble or aggregated inclusion bodies
- 3. Periplasm: soluble or aggregated inclusion bodies

Understanding the **Options** Essential Process Requirements **Recommended Filter Filter Characteristics Expressed Protein Clarification** Cell Removal **Depth Filtration** • Separation of cells from fermenter Double-layer broth and product recovery in • Better suited for small to medium size fermenters up to 1,000 L or Millistak+ HC Filters filtrate fluid larger volumes with low usage rates of less than 10 batches/year • Double-layer design enhances loading capacity and filtrate quality • High solids content in feed stream, (Grade COHC or DOHC) which makes centrifugation a • Unique configuration allows compression of multiple process steps into viable option one, lowering overall filtration costs • Selection of COHC or DOHC media grade depends on particle size • Feed stream quality can vary depending upon cell type and distribution in feed solution. Choice should be based upon small-scale culture conditions testing **TFF with Microfiltration Membrane** Prostak Open-Channel • Open-channel design ideal for fluids containing high cell densities Modules with 0.22 µm or and solids 0.1 µm Durapore Membrane • High flux at low transmembrane pressure allows volume reduction as fluid gets concentrated Robust construction for multiple use • Validated for multiple SIP cycles • Selection of 0.22 µm or 0.1 µm membrane depends on particle size distribution in feed solution. Choice should be based upon small-scale testing. ALTERNATIVE: For small volumes with low cell densities, Pellicon V Screen Cassettes with 0.22 µm or 0.1 µm Durapore Membrane should be tested in your small-scale trials.

Inclusion Body Clarification

- Harvest/Clarification
- Recovery of Inclusion Bodies post cell lysis and before solubilization step
- Elimination of waste fluid in the filtrate
- High solids content in feed stream, which makes centrifugation a viable technology option
- Feed stream quality can vary depending on cell type and culture conditions

TFF with Microfiltration Membrane

- Prostak Open-Channel Modules with 0.22 µm or
 - 0.1 µm Durapore Membrane
- Open-channel design accommodates high loading capacity and retention for haze removal post refolding
 - High flux at low transmembrane pressure
 - Robust construction allows multiple use
 - Validated for multiple SIP cycles
 - Selection of 0.22 µm or 0.1 µm membrane depends on particle size distribution in feed solution. Choice should be based upon small-scale testing.

ALTERNATIVE: For small volumes with low cell densities, Pellicon V Screen Cassettes with 0.22 µm or 0.1 µm Durapore Membrane should be tested in your small-scale trials.

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Understanding the **Options** continued

Essentia	Process	Requirements	
----------	---------	--------------	--

Protein Refold Pool Clarification

Clarification

- Removal of haze formed during refold process after product protein solubilization
- Mostly small sub-micron particles • Some fluid variability depending
- on refold process conditions

Triple-layer Millistak+ HC Filters

Recommended Filter

- (Grade A1HC or B1HC)
- Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention
- Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step
- Unique design enables the compression of multiple process steps into one, lowering overall filtration costs
- The selection of Grade A1HC or B1HC depends on the fluid particle size distribution and should be based on small-scale testing

Intracellular Protein Clarification

Cell Harvest

- Cell recovery from the fermenter broth, elimination of waste fluid in the filtrate
- High solids content in feed stream, which makes centrifugation a viable technology option
- Feed stream quality can vary depending on cell type and culture conditions

Lysate Clarification

- Removal of debris, particles and colloids generated during the lysis step, and product recovery in filtrate fluid
- Feed stream quality can vary depending on cell culture type and lysis conditions
- Challenging separation due to large amount of particles and wide range in size
- Typically requires several process steps in series (primary clarification then polishing filtration)
- Centrifugation is a viable option as first separation step, but still requires downstream polishing filtration

TFF with Microfiltration Membrane

- Prostak Open-Channel Modules with 0.22 µm or 0.1 µm Durapore Membrane
- Open-channel design ideal for fluids containing high cell densities and solids
- High flux at low transmembrane pressure
- Robust construction allows multiple use
- Validated for multiple SIP cycles

Filter Characteristics

• Selection of 0.22 µm or 0.1 µm membrane depends on particle size distribution in feed solution. Choice should be based upon small-scale testina.

Primary Clarification - TFF with Microfiltration Membrane

- Prostak Open-Channel Modules with 0.22 µm or 0.1 µm Durapore Membrane
- Open-channel design ideal for fluids with high solids levels

• More suited for lower cell density and solid content fluids

- High flux at low transmembrane pressure
- Robust construction allows multiple use Validated for multiple SIP cycles
- Selection of 0.22 µm or 0.1 µm membrane depends on particle size distribution in feed solution. Choice should be based upon small-scale testing.
- Pellicon V Screen Cassettes (8) with 0.22 µm or 0.1 µm Durapore Membrane, or
 - Suspended screen in feed channel allows higher turbulence enhancing separation process • Complete range of devices for easy scale-up 1,000 kD Biomax Membrane
 - Selection of 0.22 µm, 0.1 µm or 1,000 kD membrane depends on particle size distribution in feed solution. Choice should be based upon small-scale testing.

Polishing Filtration – Depth Filtration

Millistak+ HC Filters

Triple-layer

• Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention • Higher filtrate quality allows smaller size requirements for downstream

(Grade A1HC or B1HC)

- sterilizing-grade filtration step • Unique design enables the compression of multiple process steps into one, lowering overall filtration costs
- The selection of Grade A1HC or B1HC depends on the fluid particle size distribution and should be based on small-scale testing.

Essential Process Requirements	Recommended Filter	Filter Characteristics
Sterile Filtration		
Bioburden Reduction	-	
 Reduces bioburden Protects downstream chromatography and UF/DF steps Maintains yield of dilute protein and preserves purity Sterilizing-grade filtration required 	3 Single-layer Durapore 0.22 µm PVDF Filters	 Sterilizing-grade PVDF membrane won't bind valuable protein 100% Integrity tested to ensure proven performance Can be integrity testable on-site Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and, in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	3 Millipore Express SHC 0.5 μm + 0.2 μm PES Filters	 Sterilizing-grade PES membrane providing broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site Although double-layer 0.5 µm + 0.2 µm (SHC) is typical for this application, single-layer 0.2 µm (SHF) is also available. The degree of protection required for the downstream process and the plugging characteristics of the fluid will guide this selection. Choice should be based on small-scale testing.



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
Pellicon V Screen Mini Cassettes		
Durapore 0.22 µm membrane Durapore 0.1 µm membrane Biomax 1,000 kD membrane	0.1 m ²	P2GVPPV01 P2VVPPV01 P2B01/MV01
Prostak 2-stack Modules		
Durapore 0.22 µm membrane Durapore 0.1 µm membrane	0.17 m ²	PSGVAG021 PSVVAG021
Millistak+ Mini Capsules Double-layer Grade DOHC Double-layer Grade COHC Triple-layer Grade B1HC Triple-layer Grade A1HC	23 cm ²	MD0HC23HH3 MC0HC23HH3 MB1HC23HH3 MA1HC23HH3
OptiScale Capsules Durapore 0.22 µm membrane Millipore Express SHF 0.2 µm membrane Millipore Express SHC 0.5 µm + 0.2 µm membrane	13.8 cm ²	SVGLA47FF3 SGEPA47FF3 SHGEA47FF3

Filter Quick Reference Guide continued

ecommended Filters Small-Scale Processing <100 L Device (area/filter) Catalogue No.			Large-Scale Processing >100 L Device (area/filter) Catalogue No		
TFF MF		g		g	
Pellicon V Screen Cassettes					
Durapore 0.1 µm membrane	Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2VVPPV01 P2VVPPV05	Maxi Cassette (2 m²)	P2VVPPV20	
Durapore 0.22 µm membrane	Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2GVPPV01 P2GVPPV05	Maxi Cassette (2 m²)	P2GVPPV20	
Biomax 1,000 kD membrane	Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2B01MV01 P2B01MV05	Maxi Cassette (2 m ²)	P2B01MV20	
Prostak Open-Channel Modules					
Durapore 0.22 µm membrane	2-stack (0.17 m²) 4-stack (0.33 m²)	PSGVAG021 PSGVAG041	10-stack (0.84 m²) 20-stack (1.7 m²)	PSGVAG101 SK2P484E0	
Durapore 0.1 µm membrane	2-stack (0.17 m²) 4-stack (0.33 m²)	PSVVAG021 PSVVAG041	10-stack (0.84 m²) 20-stack (1.7 m²)	PSVVAG101 SK2P127E1	
Depth Filtration					
Triple-layer Millistak+ HC Filters Grade A1HC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MA1HC01FS1 MA1HC05FS1	10-cell Pod (1 m²)	MA1HC10FS1	
	2-cell 16-inch stack (0.45 m ²)	KA1HC10FF1 LA1HCH6S6	8-cell 16-inch stack (1.8 m ²)	LA1HCG6S2	
Grade B1HC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MB1HC01FS1 MB1HC05FS1 KB1HC10FF1	10-cell Pod (1 m²)	MB1HC10FS1	
	2-cell 16-inch stack (0.45 m ²)	LB1HCH6S6	8-cell 16-inch stack (1.8 m ²)	LB1HCG6S2	
Double-layer Millistak+ HC Filters Grade COHC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MCOHC01FS1 MCOHC05FS1 KCOHC10FF1	10-cell Pod (1 m²)	MCOHC10FS1	
	2-cell 16-inch stack (0.45 m ²)	LCOHCH6S6	8-cell 16-inch stack (1.8 m²)	LCOHCG6S2	
Grade D0HC	1-cell Pod (0.1 m ²) 5-cell Pod (0.5 m ²)	MDOHC01FS1 MDOHC05FS1	10-cell Pod (1 m²)	MDOHC10FS1	
	10-inch Opticap (650 cm²) 2-cell 16-inch stack (0.45 m²)	KDOHC10FF1 LDOHCH6S6	7-cell 16-inch stack (1.6 m²)	LDOHCG6S2	
Sterilizing-grade Filtration					
Durapore 0.22 µm PVDF Filters	Opticap XL2 Capsule (0.09 m²) Opticap XL4 Capsule (0.19 m²) Opticap XL5 Capsule (0.35 m²) 5-inch Cartridge (0.35 m²)	KVGLA02TT3 KVGLA04TT3 KVGLA05TT1 CVGL75S01	Opticap XL10 Capsule (0.69 m ²) Opticap XLT10 Capsule (0.69 m ²) Opticap XLT20 Capsule (1.4 m ²) Opticap XLT30 Capsule (2.1 m ²) 10-inch Cartridge (0.69 m ²) 20-inch Cartridge (1.4 m ²) 30-inch Cartridge (2.1 m ²)	KVGLA10TT1 KVGLA1TTT1 KVGLA2TTT1 KVGLA3TTT1 CVGL71TP3 CVGL72TP3 CVGL73TP3	
Millipore Express SHC 0.5 µm + 0.2 µm PES Filters	Opticap XI.3 Capsule (0.13 m²) Opticap XI.5 Capsule (0.24 m²) 5-inch Cartridge (0.24 m²)	KHGEA03TT3 KHGEA05TT1 CHGE75TS3	Opticap XL10 Capsule (0.49 m ²) Opticap XLT10 Capsule (0.49 m ²) Opticap XLT20 Capsule (0.98 m ²) Opticap XLT30 Capsule(1.47 m ²) 10-inch Cartridge (0.49 m ²) 20-inch Cartridge (0.98 m ²) 30-inch Cartridge (1.47 m ²)	KHGEA10TT1 KHGEA1TTT1 KHGEA2TTT1 KHGEA3TTT1 CHGE71TS3 CHGE72TS3 CHGE73TS3	

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.



Microbial Cell Culture Clarification

Mammalian Cell Culture Clarification

Mammalian cells are cultured by a variety of methods at a range of volumes for the production of therapeutic and diagnostic proteins. The cells are grown in a bioreactor or fermentation vessel. The first step in the purification process is the removal of whole cells, cell debris, and particulates prior to further downstream unit operations.

Understanding Cell Lines

Cell lines typically employed for mammalian cell culture include CHO, NSO hybridoma cells, baby hamster kidney (BHK) cells, and PER.C6[™] human cells. The most commonly employed mammalian cell line used for mammalian cell culture at production scale volumes are the CHO and NSO cell lines. These cell types are relatively easy to genetically engineer, have been extensively characterized, are relatively easy to grow at large scale, and can excrete high titers of recombinant proteins in solution. Both CHO and NSO cell lines can produce high protein expression levels, however, cell viability tends to decline with high protein expression levels. Low cell viabilities burden downstream purification with cell debris. DNA. host cell protein and other impurities. NSO cell lines require additional media components to support cell growth (i.e. cholesterols, lipids, etc.) that can affect downstream processing. Hybridoma cells have relatively low protein expression levels (<100 mg/L) and are typically grown to low cell viabilities (<30%) which complicates the harvest operation.

Cell Culture Media Types

Cell culture medium typically contains amino acids, vitamins, electrolytes and may contain hormones, growth factors, plant hydrolysates, animal serum, antibiotics, antioxidants, antifoams, cell stabilizers and other components.

Types of media include serum based, serum free, animal free, and protein free or chemically defined. Serum based and serum free media are widely used since they can be used to grow a broad range of cell types and cell lines such as CHO or NSO cells.

For details on Tank Venting (5), see page 70.


Comparison of Cell Culture Operating Modes

Operating Mode	Batch	Fed-Batch	Perfusion
Media Addition	Initial	Periodic	Continuous
Fluid Harvest	Final	Final	Continuous
Benefits	Less cell debris, lower risk of contamination	High titer	High productivity Low capital cost
Disadvantages	Fair productivity Frequent equipment turnover	Maintaining sterility in bioreactor Medium cell debris	Maintaining sterility in bioreactor and in the primary clarifier High cell debris

Cell Culture Characterization

Evaluating the cell culture characteristics is a critical step in developing an effective process. Below are some generally accepted culture properties that can be used to help guide the technology selection.

Batch	Fed-Batch	Perfusion
3–7 Days	7–15 Days	>20 Days
Low <1%	Medium 2–3%	High >3%
Low <3 x 10° cells/mL	Medium to High 5–15 x 10° cells/mL	High >10-15 x 10° cells/mL
High >90%	Medium to High 20–90%	Medium to Low <50%
Low	Medium to High	High
Low <200 NTU	High 500 to >1,000 NTU	Very High >>1,000 NTU
Easy	Medium	Difficult
	<1% Low <3 x 10° cells/mL High >90% Low Low <200 NTU	LowMedium<1%



Info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289 Understanding the **Options**

Recommended Filter	Filter Characteristics
Double-layer Millistak+ HC Filters (Grade D0HC or C0HC)	 For bioreactors volumes up to 1,000 L or larger volumes with low usage rates of less than 10 batches/year Double layer design enhances loading capacity and filtrate quality Unique configuration allows compression of multiple process steps into one, lowering overall filtration costs. Selection of COHC or DOHC media grade depends on particle size distribution in feed solution. Choice should be based upon small-scale testing.
Prostak Open-Channel Modules with 0.22 µm or 0.65 µm Durapore Membrane	 Best suited for large bioreactors >1,000 L or bioreactors with high usage rates of more than 10 batches/year Open-channel design accommodates fluids containing low to medium cell density and solids High flux at low transmembrane pressure Robust construction allows multiple use Validated for multiple SIP cycles Selection of 0.22 µm or 0.65 µm membrane depends on particle size distribution in feed solution. Choice should be based upon small-scale testing.
	 Double-layer Millistak+ HC Filters (Grade DOHC or COHC) Prostak Open-Channel Modules with 0.22 µm or 0.65 µm Durapore

Secondary Clarification or Polishing

 Feed stream quality can vary 	•	
 reed stream quality can vary depending on cell type, culture conditions, and primary clarification technology 	3 Triple-layer Millistak+ HC Filters (Grades A1HC or B1HC)	 Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention High filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Unique design enables the compression of multiple process steps into one, lowering overall filtration costs The selection of grade A1HC or B1HC depends on the fluid particle size distribution and should be based on small-scale testing.
	ALTERNATIVE: If process hardware die prefilters in your small-scale trials.	ctates the use of pleated cartridge filters, Millipore suggests testing Polysep II multi-layer
Bioburden Reduction	-	
 Reduces bioburden Protects downstream chromatography and UF/DF steps Maintains yield of dilute protein and preserves purity Sterilizing-grade filtration recommended 	Single-layer Durapore 0.22 µm Filters	 Sterilizing-grade low-protein binding PVDF membrane 100% Integrity testing to ensure performance Can be integrity testable on-site Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and, in single-layer or multi-layer configurations to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	 Double-layer Millipore Express SHC 0.5 μm + 0.2 μm Filters 	 Sterilizing-grade PES membrane providing broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site Although double-layer 0.5 µm + 0.2 µm (SHC) is typical for this application, single-layer 0.2 µm (SHF) filters are available. The degree of protection required for the downstream process and the plugging characteristics of the fluid will guide this selection. Choice should be based on small-scale testing.



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
Prostak 2-stack Modules		
Durapore 0.65 µm membrane Durapore 0.22 µm membrane	0.17 m ²	PSDVAG021 PSGVAG021
Millistak+ Mini Capsules		
Double-layer Grade DOHC		MD0HC23HH3
Double-layer Grade COHC	23 cm ²	MC0HC23HH3
Triple-layer Grade B1HC	20 611	MB1HC23HH3
Triple-layer Grade A1HC		MA1HC23HH3
OptiScale Capsules		
Durapore 0.22 µm membrane		SVGLA47FF3
Millipore Express SHF 0.2 µm membrane		SGEPA47FF3
Millipore Express SHC 0.5 µm + 0.2 µm membrane	13.8 cm ²	SHGEA47FF3
Polysep II W1 1.0 µm + 0.2 µm + 0.1 µm media		SGW1A47FF3
Polýsep II W3 1.0 µm + 0.2 µm media		SGW3A47FF3
Polygard DF 5.0 µm 2-inch cartridges	_	DF05M2S03

Recommended Filters

Recommended Filters	Small-Scale Processing <100 L		Large-Scale Processing >100 L	
Media/Membrane	Device (area/filter)	Catalogue No.	Device (area/filter)	Catalogue No.
TFF MF				
Prostak Open-Channel Modules 0.65 µm Membrane	2-stack (0.17 m²) 4-stack (0.33 m²)	PSDVAG021 PSDVAG041	10-stack (0.84 m²) 20-stack (1.7 m²)	PSDVAG101 SK2P446E0
0.22 µm Membrane	2-stack (0.17 m²) 4-stack (0.33 m²)	PSGVAG021 PSGVAG041	10-stack (0.84 m²) 20-stack (1.7 m²)	PSGVAG101 SK2P484E0
Depth Filtration				
Triple-layer Millistak+ HC Grade A1HC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MA1HC01FS1 MA1HC05FS1 KA1HC10FF1	10-cell Pod (1 m²)	MA1HC10FS1
	2-cell stack (0.45 m ²)	LA1HCH6S6	8-cell stack (1.8 m ²)	LA1HCG6S2
Grade B1HC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MB1HC01FS1 MB1HC05FS1 KB1HC10FF1	10-cell Pod (1 m²)	MB1HC10FS1
	2-cell stack (0.45 m ²)	LB1HCH6S6	8-cell stack (1.8 m ²)	LB1HCG6S2
Double-layer Millistak+ HC Filters Grade C0HC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MC0HC01FS1 MC0HC05FS1 KC0HC10FF1	10-cell Pod (1 m²)	MCOHC10FS1
	2-cell stack (0.45 m ²)	LCOHCH6S6	8-cell stack (1.8 m ²)	LCOHCG6S2
Grade D0HC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²) 10-inch Opticap (650 cm²)	MDOHC01FS1 MDOHC05FS1 KDOHC10FF1	10-cell Pod (1 m²)	MDOHC10FS1
	2-cell stack (0.45 m ²)	LDOHCH6S6	7-cell stack (1.6 m ²)	LDOHCG6S2
Sterilizing-grade Filtration				
Durapore 0.22 µm PVDF Filters	Opticap XL2 Capsule (0.09 m²) Opticap XL4 Capsule (0.19 m²) Opticap XL5 Capsule (0.35 m²) 5-inch Cartridge (0.35 m²)	KVGLA02TT3 KVGLA04TT3 KVGLA05TT1 CVGL75S01	Opticap XL10 Capsule (0.69 m ²) Opticap XLT10 Capsule (0.69 m ²) Opticap XLT20 Capsule (1.4 m ²) Opticap XLT30 Capsule (2.9 m ²) 10-inch Cartridge (0.69 m ²) 20-inch Cartridge (1.4 m ²) 30-inch Cartridge (2.1 m ²)	KVGLA10TT1 KVGLA1TTT1 KVGLA2TTT1 KVGLA3TTT1 CVGL71TP3 CVGL72TP3 CVGL73TP3
Millipore Express SHC 0.5 µm + 0.2 µm PES Filters	Opticap XL3 Capsule (0.13 m²) Opticap XL5 Capsule (0.23 m²) 5-inch Cartridge (0.23 m²)	KHGEA03TT3 KHGEA05TT1 CHGE75TS3	Opticap XL10 Capsule (0.49 m ²) Opticap XLT10 Capsule (0.49 m ²) Opticap XLT20 Capsule (0.98 m ²) Opticap XLT30 Capsule(1.47 m ²) 10-inch Cartridge (0.49 m ²) 20-inch Cartridge (0.98 m ²) 30-inch Cartridge (1.47 m ²)	KHGEA10TT1 KHGEA1TTT1 KHGEA2TTT1 KHGEA3TTT1 CHGE71TS3 CHGE72TS3 CHGE73TS3

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Protein and Antibody Downstream Processing

This section covers the series of operations immediately following the cell culture, lysate or refold clarification process. The first of these unit operations is a capture where the product protein is typically bound to an affinity chromatography resin and then recovered by elution with a buffer solution. Once recovered, the protein solution is further purified and concentrated through filtration or additional chromatography steps until the final solution is ready for final fill operations.

See buffer preparation, mammalian cell culture clarification, microbial cell culture clarification and aseptic processing sections for details on those operations. The primary goals for successful protein processing are:


- High product purity
- High product quality (or activity)
- Robustness (consistency from batch to batch)
- High product yield
- Controlled bioburden and endotoxin
- Economical

Cartridge filtration is used for chromatography column and TFF protection and sterile filtration. Ultrafiltration (Tangential Flow Filtration) steps are used to reduce batch volumes and exchange buffers for efficient column operation or final formulation. Sequential capture, purification and polishing columns remove impurities to achieve specified product purity with high product recovery. Efficient process design maximizes the difference between product and impurity binding. More than one type of virus clearance step (inactivation, filtration) is required to ensure product safety in mammalian cell and transgenic expression systems.

For details on Tank Venting 6, see page 70.

Other Relevant Applications

14
16
20
25
60
70



LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Understanding the **Options**

Essential Process Requirements	Recommended Filter	Filter Characteristics
Column Protection		
 Reduces bioburden levels Protects and extends the life of downstream chromatographic media Preserves product purity 	2 Durapore PVDF Filters (0.22 μm or Multilayer 0.45 μm + 0.22 μm)	 Sterilizing-grade filters assure reduction of contaminating microorganisms that shorten the life of costly chromatography media Low-binding PVDF membrane assures protein yeld 100% Integrity testing ensures quality Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. Can be integrity testable on-site
	2 Millipore Express SHF 0.2 µm PES Filters	 Sterilizing-grade PES membrane providing broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity testing ensures quality Asymmetric pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site Available in single-layer 0.2 µm (SHF) or double-layer 0.5 µm + 0.2 µm (SHC) configurations. The degree of protection required for the downstream process and the plugging characteristics of the fluid will guide this selection. Choice should be based on small-scale testing.
Viral Clearance (Optional for mammalian cell expression systems) • Ensure product safety against viruses • Highly validated and reliable technology • Maximize product recovery • Preserves product purity	 4 Viresolve NFP PVDF Filters 3 	 >4 log removal of parvovirus and other small viruses Robust PVDF membrane >98% recovery of protein up to 160 kD 100% Integrity testing assures performance Can be integrity tested on-site To enhance filter performance and capacity, Millipore suggests using the Viresolve Prefilter (3) in series
	Viresolve NFR PES Filters	 >6 log removal of retroviruses (80–120 nm) >98% recovery of protein (IgG) 100% Integrity testing assures performance Can be integrity tested on-site
 Ultrafiltration Concentration, buffer exchange and final formulation Maximize product recovery Fast, robust process able to accommodate feed fluid variations Wide chemical compatibility with cleaning agents Easily scalable from lab to manufacturing scale 	Pellicon C Screen Cassettes with Ultracel PLC Membranes	 Low feed flow requirement minimizes pumping, working and hold up volumes Highly retentive regenerated cellulose membranes offer good permeate flux and withstand process upsets Robust low binding void-free membranes provide excellent repeat performance Choose a membrane molecular weight cut-off 3–5X smaller than the protein to be retained. Choice should be based on small-scale testing.
	ALTERNATIVE: Consider using chemica chemicals are required.	ally resistant Biomax membranes when harsh cleaning and/or decontamination

Understanding the **Options** continued

Essential Process Requirements	Recommended Filter	Filter Characteristics
Sterile Filtration		
 Sterilizing-grade step to reduce bioburden Highly validated and reliable technology Preserves product purity Ensures product safety 	5 Durapore 0.22 μm PVDF Filters	 Sterilizing-grade PVDF membrane won't bind valuable protein 100% Integrity testing and thousands of existing applications assure proven performance Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. Integrity testable on-site
	Millipore Express PES Filters	 Sterilizing-grade PES membrane providing broad chemical compatibilit across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site Although double-layer 0.5 µm + 0.2 µm (SHC) is typical for this application, single-layer 0.2 µm (SHF) is also available. The degree of protection required for the downstream process and the plugging characteristics of the fluid will guide this selection. Choice should be based on small-scale testing.



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
Pellicon XL 50 Cassettes		
Biomax 30 kD membrane Ultracel PLC 30 kD membrane Ultracel PLC10 kD membrane	50 cm ²	SK1M007W01 PXC030C50 PXC010C50
OptiScale Capsules Durapore 0.22 µm membrane Multilayer Durapore 0.45 µm + 0.22 µm membrane Multipore Express SHF 0.2 µm membrane Millipore Express SHC 0.5 µm + 0.2 µm membrane	13.8 cm ²	SVGLA47FF3 SHGLA47FF3 SGEPA47FF3 SHGEA47FF3
Evaluation Kit with OptiScale-25 Capsules* Viresolve NFP membrane Viresolve NFR membrane	3.5 cm ²	SVPVA25NB9 SZRVA25NB9
OptiScale-40 Capsules Viresolve NFP Prefilter	5 cm ²	SSPVA40NB9
*Viresolve membranes are available in an Evaluation Kit containing 9 Optis and are ideal for scale-up and scale down studies.	Scale-25 Capsules, 3 each of 3	membrane lots,

		Large-Scale Processing	
Device (area/tilter)	Catalogue No.	Device (area/filter)	Catalogue No.
Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2C030C01 P2C030C05	Maxi Cassette (2.5 m²)	P2C030C25
Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2C010C01 P2C010C05	Maxi Cassette (2.5 m ²)	P2C010C25
Opticap XL2 Capsule (0.09 m²) Opticap XL4 Capsule (0.19 m²) Opticap XL5 Capsule (0.35 m²) 5-inch Cartridge (0.35 m²)	KVGLA02TT3 KVGLA04TT3 KVGLA05TT1 CVGL75S01	Opticap XL10 Capsule (0.69 m ²) Opticap XLT20 Capsule (1.4 m ²) Opticap XLT30 Capsule (2.9 m ²) 10-inch Cartridge (0.69 m ²) 20-inch Cartridge (1.4 m ²) 30-inch Cartridge (2.1 m ²)	KVGLA10TT1 KVGLA2TTT1 KVGLA3TTT1 CVGL71TP3 CVGL72TP3 CVGL73TP3
		Opticap XL10 Capsule (0.55 m ²) Opticap XLT20 Capsule (1.10 m ²) Opticap XLT30 Capsule (1.65 m ²) 10-inch Cartridge (0.55 m ²) 20-inch Cartridge (1.10 m ²) 30-inch Cartridge (1.65 m ²)	KHGLA10TT1 KHGLA2TTT1 KHGLA3TTT1 CHGL71TP3 CHGL72TP3 CHGL73TP3
Opticap XL3 Capsule: Autoclavable (0.13 m ²) Gamma-compatible (0.13 m ²) Opticap XL5 Capsule: Autoclavable (0.23 m ²) Gamma-compatible (0.24 m ²) 5-inch Cartridge (0.23 m ²)	KHGEA03TT3 KHGEG03TT1 KHGEA05TT1 KHGEG05TT1 CHGE75TS3	Opticap XL10 Capsule: Autoclavable (0.49 m²) Gamma-compatible (0.54 m²) 10-inch Cartridge (0.49 m²) Opticap XLT30 Capsule: Autoclavable (1.47 m²) Gamma-compatible (1.63 m²) 30-inch Cartridge (1.47 m²)	KHGEA10TT1 KHGEG10TT1 CHGE71TS3 KHGEA3TTT1 KHGEG3TTT1 CHGE73TS3
Opticap XL3 Capsule: Autoclavable (0.16 m ²) Gamma-compatible (0.17 m ²) Opticap XL5 Capsule: Autoclavable (0.29 m ²) Gamma-compatible (0.31 m ²) 5-inch Cartridge (0.29 m ²)	KGEPA03TT3 KGEPG03TT1 KGEPA05TT1 KGEPG05TT1 CGEP75TP3	Opticap XL10 Capsule: Autoclavable (0.54 m ²) Gamma-compatible (0.57 m ²) 10-inch Cartridge (0.54 m ²) Opticap XLT30 Capsule: Autoclavable (1.62 m ²) Gamma-compatible (1.71 m ²) 30-inch Cartridge (1.62 m ²)	KGEPA10TT1 KGEPG10TT1 CGEP71TP3 KGEPA3TTT1 KGEPG3TTT1 CGEP73TP3
n systems only)			
10-inch Cartridge (0.48 m²) Opticap XLT20 Capsule (0.97 m²)	CVPV71TP1 KVPVA2TTT1	Opticap XIT30 Capsule (1.45 m²) 20-inch Cartridge (0.97 m²) 30-inch Cartridge (1.45 m²) olumes >750 L.	KVPVA3TTT1 CVPV72TP1 CVPV73TP1
Opticap (850 cm²)	KSPV01FF1	Opticap (850 cm²)	KSPV01FF1
		Opticap XL10 Capsule (0.54 m ²) Opticap XLT10 Capsule (0.54 m ²) 10-inch Cartridge (0.54 m ²) Opticap XLT20 Capsule (0.86 m ²) 20-inch Cartridge (0.86 m ²) Opticap XLT30 Capsule (1.29 m ²) 30-inch Cartridge (1.29 m ²)	KZRVA 10TT1 KZRVA 1TTT1 CZRV7 1TP1 KZRVA2TTT1 CZRV72TP1 KZRVA3TTT1 CZRV73TP1
	Device (area/filter) Mini Cassette (0.1 m²) Cassette (0.5 m²) Mini Cassette (0.1 m²) Cassette (0.5 m²) Opticap XL2 Capsule (0.09 m²) Opticap XL4 Capsule (0.19 m²) Opticap XL5 Capsule (0.35 m²) 5-inch Cartridge (0.35 m²) Sinch Cartridge (0.35 m²) Opticap XL3 Capsule: Autoclavable (0.13 m²) Gamma-compatible (0.13 m²) Opticap XL3 Capsule: Autoclavable (0.23 m²) Gamma-compatible (0.24 m²) 5-inch Cartridge (0.23 m²) Gamma-compatible (0.17 m²) Opticap XL3 Capsule: Autoclavable (0.16 m²) Gamma-compatible (0.17 m²) Opticap XL3 Capsule: Autoclavable (0.29 m²) Gamma-compatible (0.17 m²) Opticap XL3 Capsule: Autoclavable (0.29 m²) Gamma-compatible (0.31 m²) 5-inch Cartridge (0.29 m²) Gamma-compatible (0.31 m²) 5-inch Cartridge (0.29 m²) Gamma-compatible (0.31 m²) 5-inch Cartridge (0.48 m²) Opticap XL10 Capsule (0.48 m²) Opticap XL10 Capsule (0.48 m²) Opticap	Mini Cassette (0, 1 m²) Cassette (0, 5 m²)P2C030C01 P2C030C05Mini Cassette (0, 1 m²) Cassette (0, 5 m²)P2C010C01 P2C010C05Opticap XI2 Capsule (0, 09 m²) Opticap XI5 Capsule (0, 35 m²)KVGLA02TT3 KVGLA05TT1 CVGL75S01Opticap XI3 Capsule: Autoclavable (0, 13 m²) Gamma-compatible (0, 13 m²) Copticap XI5 Capsule: Autoclavable (0, 23 m²)KHGEA03TT3 KHGEG03TT1 CVGL75S01Opticap XI3 Capsule: Autoclavable (0, 23 m²)KHGEA03TT3 KHGEG03TT1 CHGE75TS3Opticap XI3 Capsule: Autoclavable (0, 23 m²)KHGEA03TT3 KHGEG05TT1 CHGE75TS3Opticap XI3 Capsule: Autoclavable (0, 23 m²)KHGEA03TT3 KGEPA03TT3 KGEPA03TT3 CHGE75TS3Opticap XI3 Capsule: Autoclavable (0, 16 m²) Gamma-compatible (0, 24 m²)KGEPA03TT3 KGEPG03TT1 CHGE75TS3Opticap XI3 Capsule: Autoclavable (0, 29 m²)KGEPA03TT3 KGEPG03TT1 CGEP75TP3Opticap XI3 Capsule: Autoclavable (0, 29 m²)KGEPA03TT3 KGEPG05TT1 CGEP75TP3 A -inch Opticap (0.077 m²) Opticap XI10 Capsule (0.48 m²) CVPV21TP1 Opticap XI10 Capsule (0.097 m²) KVPVA1TT1 Millipore suggests using multiple cartridges or capsules for v Opticap (850 cm²)Opticap (850 cm²)KSPV01FF14-inch Opticap Capsule (0.093 m²)KZRV04TC3	Device (area/filter) Catalogue No. Device (area/filter) Mini Cassette (0.1 m²) P2C030C01 Maxi Cassette (2.5 m²) Cassette (0.5 m²) P2C010C01 Maxi Cassette (2.5 m²) Opticap XL2 Capsule (0.09 m²) P2C010C01 Maxi Cassette (2.5 m²) Opticap XL2 Capsule (0.09 m²) KVGIA02TT3 Opticap XL10 Capsule (0.69 m²) Opticap XL2 Capsule (0.19 m²) KVGIA03TT3 Opticap XL30 Capsule (2.9 m²) Opticap XL2 Capsule (0.35 m²) KVGIA03TT3 Opticap XL30 Capsule (2.9 m²) Opticap XL3 Capsule (0.35 m²) KVGIA03TT3 Opticap XL30 Capsule (2.9 m²) S-inch Cartridge (0.35 m²) KVGIA03TT3 Opticap XL30 Capsule (0.65 m²) Opticap XL3 Capsule: KHGEA03TT3 Autoclavable (0.15 m²) Autoclavable (0.13 m²) KHGEA03TT1 Cantridge (1.16 m²) Gamma compatible (0.13 m²) KHGEA03TT1 Cantridge (1.47 m²) Opticap XL3 Capsule: KHGEA03TT1 Autoclavable (0.49 m²) Autoclavable (0.23 m²) KHGEA03TT1 Cantridge (1.47 m²) Opticap XL3 Capsule: KHGEA03TT1 Autoclavable (0.57 m²) Autoclavable (0.24 m²) KHGEA03TT1

*Viresolve Prefilter will be available in Millipore's Pod technology late 2005.

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.


Millipore offers a comprehensive line of chromatography columns, systems and media. Contact Millipore for details.

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Serum

Animal sera contain important growth factors necessary for the effective culture of mammalian cells. Serum can vary significantly, depending on the species and age of the donor animal, seasonal changes and animal diet. Fetal bovine sera tends to be relatively easy to filter while calf and adult bovine sera requires prefiltration or greater filtration area. Non-bovine sera (equine, porcine, etc) tend to have high concentrations of colloids and thus require filtration. For difficult serum, a robust clarification step using Millistak+ depth filter can be added. Depending on the nature and volume of the serum stream filters may need to be run in series to assure proper contaminant removal.

For details on Tank Venting (6), see page 70.



Understanding the **Options**

Essential Process Requirements	Recommended Filter	Filter Characteristics
Clarification and Prefiltration		
 Clarification and Pretiltration Remove lipids, colloidal and particulate contaminants Operate consistently at high differential pressures and flow rates Extend the lifetime of final filters Must be able to withstand multiple steam-in-place or hot water sanitization cycles Run efficiently to ensure process economics 	Triple-layer Millistak+ HC Filters (Grade A1HC or B1HC)	 Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Unique design enables the compression of multiple process steps into one, lowering overall filtration costs The selection of Grade A1HC or B1HC depends on the fluid particle size distribution and should be based on small-scale testing.
	Clarigard Filters (0.5 μm, 1.0 μm or 3.0 μm)	 Polypropylene prefilter for robust particle and colloid removal Validated for multiple sanitization and SIP cycles Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Non-fiber releasing structure preserves product purity Available in a wide-range of pore sizes to accommodate the needs of each user. Choice should be made based on small-scale testing.

Essential Process Requirements	Recommended Filter	Filter Characteristics
Clarification and Prefiltration continued	3 Double-layer Milligard Filters (Grade SS, 0.5 μm + 0.2 μm, or Grade SC, 1.2 μm + 0.5 μm)	 Double-layer pleated configuration of mixed esters of cellulose membranes remove particles and colloids High porosity membranes operate at high flow rates and low pressure drops Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Robust construction validated to withstand multiple SIP or hot water sanitization cycles Available in a variety of pore sizes to accommodate the needs of each user. Grade SS is commonly used to protect downstream 0.22 µm sterilizing-grade filters. Grade SC is better suited to protect 0.45 µm membrane filters. Choice should be made based on small-scale testing.
	3 Polysep II Filters (Grade W3, 1 μm + 0.2 μm)	 Depth filter consisting of a borosilicate glass layer and a layer of mixed esters of cellulose membranes Robust prefilter for concentrated solutions across a full range of flow rates High particle-loading capacity and retention Able to withstand multiple SIP or hot water sanitization cycles Non-fiber releasing
inal Filtration Reduce bacteria and mycoplasma to ensure long term storage and stability Eliminate the risk of adventitious infectious agents Operate consistently at high differential pressures and flow rates Must be able to withstand multiple steam-in-place or hot water sanitization cycles Run efficiently to ensure process economics	Durapore CBR 0.1 μm Filters	 Low protein-binding PVDF membrane Retentive membrane reduces bioburden Low extractables and non-fiber releasing PVDF chemistry preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing ensures quality Validated for multiple SIP and hot water sanitization cycles Although 0.1 µm is typical for this application, Durapore CBR 0.2 µm filters are also available. Choice should be based on small-scale screening.
	3 Durapore 0.1 μm Filters	 Sterilizing-grade PVDF membrane will assure bioburden and mycoplasma clearance 100% Integrity testing and thousands of existing applications assure proven performance Integrity testable on-site Although 0.1 µm is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	 Millipore Express SHR 0.1 µm Filters (with or without prefilter layer) 	 Designed to remove high levels of mycoplasma and bacteria over a range of moderately plugging to highly fouling streams Asymmetric pore structure delivers extremely high flow rates at low pressure drop Sterilizing-grade PES membrane provides broad chemical compatibility across a wide pH range (1–14) 100% integrity tested to ensure quality Robust construction validated for multiple SIP cycles Can be integrity tested on-site Available in single-layer 0.1 µm or double-layer 0.1 µm with prefilter layer 0.1 µm configurations. The degree of protection required for the downstream process and the plugging characteristics of the fluid will guide this selection. Choice should be based on small-scale testing.

Serum



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
OptiScale Capsules		
Double-layer Milligard SC 1.2 µm + 0.5 µm membrane		SWSCA47FF3
Double-layer Milligard SS 0.5 µm + 0.2 µm membrane		SWSSA47FF3
Double-layer Polysep II W3 1.0 µm + 0.2 µm membrane		SGW3A47FF3
Durapore 0.1 µm membrane	13.8 cm ²	SVVLA47FF3
Single-layer Millipore Express SHR membrane		SVEPA47FF3
Double-layer Millipore Express SHR membrane		SHVEA47FF3
Millistak+ Mini Capsules		
Triple-layer Grade A1HC	23 cm ²	MA1HC23HH3
Triple-layer Grade B1HC	25 CIII	MB1HC23HH3
Opticap XL1 Capsules		
Clarigard 0.5 µm	1-inch*	K005A51TT1
Clarigard 1.0 µm	1-inch*	K010A51TT1
Clarigard 3.0 µm	1-inch*	K030A51TT1
*Filter element size		

Recommended Filters

Recommended Filters	Grade A1HC		Grade B1HC	
Triple-layer Millistak+ HC Filters	Area/Filter	Catalogue No.	Area/Filter	Catalogue No.
1-cell Pod	0.1 m ²	MA1CH01FS1	0.1 m ²	MB1HC01FS1
5-cell Pod	0.5 m ²	MA1HC05FS1	0.5 m ²	MB1HC05FS1
10-cell Pod	1.0 m ²	MA1HC10FS1	1.0 m ²	MB1HC10FS1
Opticap Capsule	650 cm ²	KA1HC10FF1	650 cm ²	KB1HC10FF1
2-cell Stack	0.45 m ²	LA1HCH6S6	0.45 m ²	LB1HCH6S6
8-cell Stack	1.8 m ²	LA1HCG6S2	1.8 m ²	LB1HCG6S2
Clarigard Filters	Filter Element Size	0.5 µm	1.0 µm	3.0 µm
Opticap XL1 Capsule	1-inch	K005A51TT1	K010A51TT1	K030A51TT1
2-inch Cartridge	2-inch	D005N0S03	D010N0S03	D030N0S03
Opticap XL5 Capsule	5-inch	K005A05TT1	K010A05TT1	K030A05TT1
Opticap XL10 Capsule	10-inch	K005A10TT1	K010A10TT1	K030A10TT1
10-inch Cartridge	10-inch	D00571S01	D01071S01	D03071S01
20-inch Cartridge	20-inch	D00572S01	D01072S01	D03072S01
30-inch Cartridge	30-inch	D00573S01	D01073S01	D03073S01
40-inch Cartridge	40-inch	D00574S01	D01074S01	D03074S01
		Grade SS	Grade SC	
Milligard Filters	Area/Filter	Catalogue No.	Catalogue No.	
Opticap XL2 Capsule	0.07 m ²	KVVSSA02TT3	KWSCA02TT3	
Opticap XL4 Capsule	0.16 m ²	KVVSSA04TT3	KWSCA04TT3	
4-inch Cartridge	0.28 m ²	CWSSM4S03	CWSCM4S03	
Opticap XL5 Capsule	0.28 m ²	KVVSSA05TT1	KWSCA05TT1	
Opticap XL10 Capsule	0.7 m ²	KWSSA10TT1	KWSCA10TT1	
Opticap XLT10 Capsule	0.7 m ²	KWSSA1TTT1	KWSCA1TTT1	
Opticap XLT20 Capsule	1.4 m ²	KWSSA2TTT1	KWSCA2TTT1	
Opticap XLT30 Capsule	2.1 m ²	KVVSSA3TTT1	KWSCA3TTT1	
10-inch Cartridge	0.7 m ²	CWSS71S03	CWSC71S03	
20-inch Cartridge	1.4 m ²	CWSS72S03	CWSC72S03	
30-inch Cartridge	2.1 m ²	CWSS73S03	CWSC73S03	
40-inch Cartridge	2.8 m ²	CWSS74S03	CGSC74S03	
	Grad			
Polysep II Filters	Area/Filter	Catalogue No.		
Opticap XL2 Capsule	0.06 m ²	KGW3A02TT3		
Opticap XL4 Capsule	0.11 m ²	KGW3A04TT3		
4-inch Cartridge	0.19 m ²	CGW3M4S03		
Opticap XL5 Capsule	0.19 m ²	KGW3A05TT1		
Opticap XL10 Capsule	0.46 m ²	KGW3A10TT1		
Opticap XLT10 Capsule	0.46 m ²	KGW3A1TTT1		
Opticap XLT20 Capsule	0.92 m ²	KGW3A2TTT1		
Opticap XLT30 Capsule	1.38 m ²	KGW3A3TTT1		
10-inch Cartridge	0.46 m ²	CGW371S03		
20-inch Cartridge	0.92 m ²	CGW372S03		
30-inch Cartridge	1.38 m ²	CGW373S03		
40-inch Cartridge	1.84 m ²	CGW374S03		

Durapore CBR Filters	Area/Filter	0.1 µm		
10-inch Cartridge	0.69 m ²	CVVI71TPS		
20-inch Cartridge	1.4 m ²	CVVI72TPS		
30-inch Cartridge	2.1 m ²	CVVI73TPS		
40-inch Cartridge	2.8 m ²	CVVI74TPS		
Durapore Sterilizing-grade Filters	Area/Filter	0.1 µm		
Opticap XL2 Capsule	0.09 m ²	KVVLA02TT3		
Opticap XL4 Capsule	0.19 m ²	KVVLA04TT3		
5-inch Cartridge	0.35 m ²	CVVL75S01		
Opticap XL5 Capsule	0.35 m ²	KVVLA05TT1		
Opticap XL10 Capsule	0.69 m ²	KVVLA10TT1		
10-inch Cartridge	0.69 m ²	CVVL71TP3		
Opticap XLT10 Capsule	0.69 m ²	KVVLA1TTT1		
20-inch Cartridge	1.4 m ²	CVVL72TP3		
Opticap XLT20 Capsule	1.4 m ²	KVVLA2TTT1		
30-inch Cartridge	2.1 m ²	CVVL73TP3		
Opticap XLT30 Capsule	2.1 m ²	KVVLA3TTT1		
40-inch Cartridge	2.8 m ²	CVVL74TP3		
Millipore Express SHR Sterilizing-grade		0.1 µm	Area/Filter	0.1 µm + Prefilter
Opticap XL3 Capsule	0.14 m ²	KVEPAO3TT3	0.12 m ²	KHVEA03TT3
Opticap XL3				
Gamma-compatible Capsule	0.14 m ²	KVEPG03TT3	0.12 m ²	KHVEG03TT3
Opticap XL5 Capsule	0.27 m ²	KVEPAO5TT1	0.22 m ²	KHVEA05TT1
Opticap XL5				
Gamma-compatible Capsule	0.27 m ²	KVEPG05TT1	0.22 m ²	KHVEG05TT1
5-inch Cartridge	0.27 m ²	CVEP75TS3	0.22 m ²	CHVE75TS3
Opticap XL10 Capsule	0.54 m ²	KVEPA 1 OTT 1	0.5 m ²	KHVEA10TT1
Opticap XLT10 Capsule	0.54 m ²	KVEPA1TTT1	0.5 m ²	KHVEG10TT1
Opticap XL10	0.54 2		0.5.2	
Gamma-compatible Capsule Opticap XLT10	0.54 m ²	KVEPG10TT1	0.5 m ²	KHVEA1TTT1
Gamma-compatible Capsule	0.54 m ²	KVEPG1TTT1	0.5 m ²	KHVEG1TTT1
10-inch Cartridge	0.54 m ²	CVEP71TS3	0.5 m ²	CHVEZ1TS3
Opticap XLT20 Capsule	1.07 m ²	KVEPA2TTT1	l m ²	KHVEA2TTT1
Opticap XLT20 Opticap XLT20	1.07 11	IN LIAZ IIII	1 111	NIT LAZ IIII
Gamma-compatible Capsule	1.07 m ²	KVEPG2TTT1	1 m ²	KHVEG2TTT1
20-inch Cartridge	1.07 m ²	CVEP72TS3	1 m ²	CHVE72TS3
Opticap XLT30 Capsule	1.0 m ²	KVEPA3TTT1	1.5 m ²	KHVEA3TTT1
Opticap XLT30 Opticap XLT30	1.0 m	RIELAUTTI	1.0 11	KINE/JOTTI
Gamma-compatible Capsule	1.6 m ²	KVEPG3TTT1	1.5 m ²	KVEPG3TTT1
			1.0 10	
30-inch Cartridge	1.6 m ²	CVEP73TS3	1.5 m ²	CHVE73TS3

*Millipore Express SHR Filters are in final development. Specifications may change. Consult technical services for details.

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Lenntech

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Plasma Fractionation

Human plasma is the source of over 700 proteins of considerable therapeutic value such as albumin, clotting factors, immunoglobulins, fibrinogen and others. The process used to extract and purify these proteins is known as plasma fractionation. Classical fractionation employs selective precipitation of proteins by manipulation of solution pH, ionic strength, temperature and ethanol content. Modern fractionation increasingly employs chromatography to make higher purity and better activity products. Contamination of plasma compounds can cause product instability as well as plugging downstream filters and should be removed via prefiltration. Clarification is used to remove contaminants prior to chromatography or UF steps, while sterilizing-grade filtration is a final step used to reduce bioburden and to sterilize heat

labile proteins. A critical step, viral clearance, ensures the removal of viruses known to have contaminated source plasma such as parvovirus, hepatitis and HIV. Specialty antibodies such as hyper-immune globulin typically include a viral clearance filtration step in their manufacturing process.

For details on Tank Venting 10, see page 70.


Final

Sterile Filtration

Final

Sterile Filtration

10



Clarification

Chromatography

Viral Clearance

Cryoprecipitation



Understanding the **Options Recommended Filter Filter Characteristics Essential Process Requirements** Albumin **Clarification and Prefiltration** Single-layer Millistak+ DE • Remove colloids, aggregated and Better suited for large volumes >500 L Filters non-product proteins, lipids and High internal surface area for maximum particle capture loading particles prior to downstream Graded density matrix allows retention of particle range purification (Grade 55DE) High porosity provides low pressure drop • Protect downstream sterilizing-grade • Although Grade 55DE is typical for this application, Millistak+ filters filters, chromatography media and are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of TFF membranes protection required for the downstream process and the plugging char-• Must be able to withstand multiple acteristics of the fluid. Choice should be based on small-scale testing. steam-in-place or hot water sanitization cycles • Run efficiently to ensure process economics Double-layer Millistak+ HC • Better suited for volumes <500 L or with low usage rates of less than Filters 10 batches/year • Double-layer design enhances loading capacity and filtrate quality (Grade COHC) • Unique configuration allows compression of multiple process steps so prefiltration may not be required. This can lower overall filtration costs. • Although Grade COHC is ideal for this application, Millistak+ filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. 4 Double-layer Milligard Filters • Double-layer pleated configuration of mixed esters of cellulose membranes provide high dirt-holding capacity and retention efficiency (Grade SS, 0.5 µm + • High porosity membranes operate at high flow rates and low 0.2 µm) pressure drops Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Robust construction validated to withstand multiple SIP or hot water sanitization cycles • Grade SS is commonly used for this application; Milligard filters are available in numerous pore sizes and, in double-layer or triple-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. 4 Double-layer Polysep II Filters • Borosilicate glass top layer enhances particle and loading capacity • Mixed esters of cellulose membrane bottom layer ensures high retention and filtrate quality (Grade W3, 1.0 µm + 0.2 µm) Robust construction validated to withstand multiple SIP or hot water sanitization cycles Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Available in a variety of pore sizes to accommodate the needs of each user. Grade W3 is commonly used to protect downstream 0.22 µm membrane filters. Choice should be made based on small-scale testing.

> LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Understanding the **Options** continued

Essential Process Requirements	Recommended Filter	Filter Characteristics
 Ultrafiltration Reduce batch volumes and exchange buffer systems for efficient column operation and final formulation Run efficiently to ensure process economics 	3 Pellicon Cassettes with Biomax 10 kD Membrane	 Biomax void-free membrane has exceptional caustic stability and excellent repeat performance Low feed flow requirement minimizes pumping, working and hold up volumes. Higher product recovery and flux Suspended screen in feed channel allows higher turbulence enhancing the separation process Complete range of Pellicon devices allow for easy scale-up
 Sterile Filtration (liquid) (Also see Aseptic Filling page 60) Sterilizing-grade filters reduce bioburden and sterilize heat labile proteins Must be able to withstand multiple steam-in-place or hot water sanitization cycles Run efficiently to ensure process economics 	5 Durapore 0.22 μm Filters	 Low protein binding sterilizing-grade PVDF membrane 100% Integrity testing and thousands of existing applications assure proven performance Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and, in single-layer or multi-layer configurations to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. Integrity testable on-site
IgG Hyper Immune	ALTERNATIVE: If a PES membrane or br SHF 0.2 μm Filters in your small-scale tr	oad chemical compatibility is a requirement Millipore suggests testing Millipore Expre ials.
 Clarification and Prefiltration Remove colloids, aggregated and non-product proteins, lipids and large particles Protect downstream sterilizing-grade filters, chromatography media and TFF membranes Must be able to withstand multiple steam-in-place or hot water sanitization cycles Run efficiently to ensure process economics 	6 Double-layer Millistak+ HC Filters (Grade COHC)	 Better suited for volumes <500 L or with low usage rates of less than 10 batches/year Double-layer design enhances loading capacity and filtrate quality Unique configuration allows compression of multiple process steps so prefiltration may not be required. This can lower overall filtration costs. Although grade COHC is ideal for this application, Millistak+ filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	Single-layer Millistak+ DE Filters (Grade 75DE)	 Better suited for large volumes >500 L High internal surface area for maximum particle capture loading Graded density matrix allows retention of particle range High porosity provides low pressure drop Although grade 75DE is typical for this application, Millistak+ filters are available in several pore sizes and, in single-layer or multi-layer configurations to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	Double-layer Milligard Filters (Grade SS, 0.5 μm + 0.2 μm)	 Double-layer pleated configuration of mixed esters of cellulose membranes provide high dirt-holding capacity and retention efficiency. High porosity membranes operate at high flow rates and low pressure drops Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Robust construction validated to withstand multiple SIP or hot water sanitization cycles Although grade SS is commonly used for this application, Milligard filters are available in numerous pore sizes and in double-layer or triple-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.

Plasma Fractionation

Essential Process Requirements	Recommended Filter	Filter Characteristics
Viral Clearance		
 Critical step to ensure removal of viruses known to have contaminated source plasma such as parvovirus, hepatitis viruses and HIV Following current regulatory guidelines, 2 orthogonal methods are normally utilized to remove or inactivate viruses Validated log removal of viruses is a dedicated process step Filtration products should easily scale-up and down for simple validation 	8 Viresolve NFR Filters	 >6 log removal of retroviruses (80–120 nm) >98% recovery of protein (IgG) 100% Integrity testing assures performance Robust PES membrane Can be integrity tested on-site
	8 Viresolve NFP Filters18	 >4 log removal of parvovirus and other small viruses >98% recovery of protein up to 160kD Robust PVDF membrane 100% Integrity testing assures performance Can be integrity tested on-site To enhance filter performance and capacity, Millipore suggests using the Viresolve Prefilter ⁽¹⁾ in series.
Ultrafiltration		
 Reduce batch volumes and exchange buffer systems for efficient column operation and final formulation Run efficiently to ensure process economics 	Pellicon Cassettes with Biomax 30 kD Membrane or Ultracel PLC 30 kD Membrane	 Low feed flow requirement minimizes pumping, working and hold up volumes Higher product recovery and flux Highly retentive void-free membranes offer good permeate flux and withstand process upsets Robust low binding void-free Ultracel PLC membranes provide excellent repeat performance Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing.
Sterile Filtration		
 Sterile Filtration (Also see Aseptic Filling page 60) Sterilizing-grade filters reduce bioburden and sterilize heat labile proteins Must be able to withstand multiple steam-in-place or hot water sanitization cycles Run efficiently to ensure process economics 	Durapore 0.22 μm Filters	 Sterilizing-grade PVDF low-binding membrane is ideal when adsorption is a concern 100% Integrity testing and thousands of existing applications assure proven performance Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. Integrity testable on-site
	Millipore Express PES Filters	 Sterilizing-grade PES membrane providing broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates even with clogging streams Can be integrity tested on-site Available in single-layer 0.2 µm (SHF) or double-layer 0.5 µm + 0.2 µm (SHC) configurations. The degree of protection required for the downstream process and the plugging characteristics of the fluid will guide this selection. Choice should be based on small-scale testing.
		downstream process and the plugging characteristics of the fluid will

LENNTECH info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289

Understanding the **Options** continued

Essential Process Requirements	Recommended Filter	Filter Characteristics
Clotting Factors		
Clarification and Prefiltration		
 Remove colloids, aggregated and non-product proteins, lipids and particles prior to downstream purification Protect downstream sterilizing-grade filters, chromatography media and TFF membranes Must be able to withstand multiple steam-in-place or hot water sanitization cycles Run efficiently to ensure process economics 	Single-layer Millistak+ DE Filters(Grade 65DE)	 Better suited for large volumes >500 L High internal surface area for maximum particle capture loading Graded density matrix enables retention of a wide range of particle sizes High porosity provides low pressure drop Although Grade 65DE is typical for this application, Millistak+ filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	15 Double-layer Milligard Filters (Grade SC, 1.2 μm + 0.5 μm)	 Double-layer pleated configuration of mixed esters of cellulose membranes provide high dirt-holding capacity and retention efficiency High porosity membranes operate at high flow rates and low pressure drops Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Robust construction validated to withstand multiple SIP or hot water sanitization cycles Grade SC is commonly used for this application; Milligard filters are available in numerous pore sizes and in single-layer or double-layer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	ALTERNATIVE: If adsorption is a concerr running Durapore 0.45 µm filters in you	n, or a robust bioburden reduction is needed before the final filter Millipore suggests r small-scale trials.
Viral Clearance		
 Critical step to ensure removal of viruses known to have contaminated source plasma such as parvovirus, hepatitis viruses and HIV Following current regulatory guidelines, 2 orthogonal methods are normally utilized to remove or inactivate viruses Validated log removal of viruses is a dedicated process step. 	13 Viresolve NFR Filters	 >6 log removal of retroviruses (80–120 nm) >98% recovery Utilizes size exclusion technology Robust PES membrane 100% integrity tested to ensure performance Can be integrity tested on-site
a dedicated process step • Filtration products should easily scale-up and down for simple validation	13 Viresolve NFP Filters18	 >4 log removal of parvoviruses and other small viruses >98% recovery of protein up to 160 kD Utilizes size exclusion technology Robust PVDF membrane 100% integrity tested to ensure performance Can be integrity tested on-site To enhance filter performance and capacity, Millipore suggests using the Viresolve Prefilter (1) series.

Essential Process Requirements	Recommended Filter	Filter Characteristics
Ultrafiltration		
 Reduce batch volumes and exchange buffer systems for efficient column operation and final formulation Run efficiently to ensure process economics 	Pellicon Cassettes with Biomax or Ultracel PLC Membranes	 Low feed flow requirement minimizes pumping, working and hold up volumes Higher product recovery and flux Highly retentive void-free membranes offer good permeate flux and withstand process upsets Robust low binding Ultracel PLC void-free membranes provide excellent repeat performance For sera with caustic stability constraints Millipore suggests Biomax membranes. For low adsorption utilize Ultracel PLC membranes. Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing
Sterile Filtration		
 (Also see Aseptic Filling page 60) Sterilizing-grade filters reduce bioburden and sterilize heat labile proteins Must be able to withstand multiple steam-in-place or hot water 	Durapore 0.22 µm Filters	 Sterilizing-grade filters assure reduction of contaminating microorgan- isms that shorten the life of costly chromatography media Low-binding PVDF membrane assures protein yield 100% Integrity testing ensures quality Although 0.22 µm is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer
sanitization cyclesRun efficiently to ensure process economics		configurations to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.

• Integrity testable on-site

ALTERNATIVE: For broad chemical compatibility and high flow rates or if PES membranes are required, Millipore suggests testing Millipore Express SHF filters in your small-scale trials.





Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
Albumin		
Pellicon XL50 Cassettes Biomax 10 kD membrane	50 cm ²	PXB010A50
OptiScale Capsules Double-layer Milligard SS 0.5 µm + 0.2 µm membrane Double-layer Polysep II W3 1.0 µm + 0.2 µm membrane Durapore 0.22 µm membrane Millipore Express SHF 0.2 µm membrane	13.8 cm ²	SWSSA47FF3 SGW3A47FF3 SVGLA47FF3 SGEPA47FF3
Millistak+ Mini Capsules Single-layer Grade 55DE Double-layer Grade COHC	23 cm^2	M55DE23HH3 MC0HC23HH3
IgG Hyper Immune Pellicon XL50 Cassettes Biomax 10 kD membrane Biomax 30 kD membrane Biomax 50 kD membrane Ultracel PLC 30 kD membrane	50 cm ²	PXB010A50 PXB030A50 PXB050A50 PXC030C50
OptiScale Capsules Double-layer Milligard SS 0.5 µm + 0.2 µm membrane Durapore 0.45 µm membrane Durapore 0.22 µm membrane Millipore Express SHF 0.2 µm membrane Double-layer Millipore Express SHC membrane	13.8 cm ²	SWSSA47FF3 SVHLA47FF3 SVGLA47FF3 SGEPA47FF3 SHGEA47FF3
Millistak+ Mini Capsules Single-layer Grade 75DE Double-layer Grade COHC	23 cm ²	M75DE23HH3 MC0HC23HH3
Evaluation Kit with OptiScale-25 Capsules* Viresolve NFP membrane Viresolve NFR membrane	3.5 cm ²	SVPVA25NB9 SZRVA25NB9
OptiScale-40 Devices Viresolve Prefilter	5 cm ²	SSPVA40NB9
Clotting Factors Pellicon XL50 Cassettes Biomax membrane is available in 5, 8,10,30,50,100,300,50 Biomax 10 kD membrane Biomax 30 kD membrane Biomax 50 kD membrane Ultracel membrane is available in 5, 10, 30, 100, 300 or 1, Ultracel PLC10 kD membrane Ultracel PLC 30 kD membrane	50 cm ²	PXB010A50 PXB030A50 PXB050A50 PXC010C50 PXC030C50
OptiScale Capsules Double-layer Milligard SC 1.2 µm + 0.5 µm membrane Durapore 0.45 µm membrane Durapore 0.22 µm membrane Millipore Express SHF 0.2 µm membrane	13.8 cm ²	SWSCA47FF3 SVHLA47FF3 SVGLA47FF3 SGEPA47FF3
Millistak+ Mini Capsules Single-layer Grade 65DE	23 cm ²	M65DE23HH3
Evaluation Kit with OptiScale-25 Capsules* Viresolve NFP membrane Viresolve NFR membrane	3.5 cm ²	SVPVA25NB9 SZRVA25NB9
OptiScale-40 Devices Viresolve Prefilter	5 cm ²	SSPVA40NB9
*Viresolve membranes are available in an Evaluation Kit containing 3 each of 3 membrane lots, and are ideal for scale-up and scale do		

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Recommended Filters Media/Membrane	Small-Scale Processing Device (area/filter) Catalogue No.		Large-Scale Processing Device (area/filter) Catalogue No.	
larification and Prefiltration				
Single-layer Millistak+ DE Grade 55DE	10-inch Opticap Capsule (930 cm²)	K55DE10FF1	12-inch, 6-cell stack (0.63 m²) 16-inch*, 16-cell stack (3.47 m²)	L55DEF2S3 L55DET6S1
Grade 65DE	10-inch Opticap Capsule (930 cm²)	K65DE10FF1	12-inch, 6-cell stack (0.63 m²) 16-inch*, 16-cell stack (3.47 m²)	L65DEF2S3 L65DET6S1
Grade 75DE	10-inch Opticap Capsule (930 cm²)	K75DE10FF1	12-inch, 6-cell stack (0.63 m²) 16-inch*, 16-cell stack (3.47 m²)	L75DEF2S3 L75DET6S1
Double-layer Millistak+ HC Filters Grade COHC	1-cell Pod (0.1 m²) 5-cell Pod (0.5 m²)	MCOHCO1FS1 MCOHCO5FS1	16-inch, 2-cell stack (0.45 m²) 16-inch, 8-cell stack (1.8 m²) 10-cell Pod (1 m²)	LCOHCH6S6 LCOHCG6S2 MCOHC10FS1
Double-layer Milligard Filters Grade SS (0.5 µm + 0.2 µm)	Opticap XL2 Capsule (0.07 m²) Opticap XL4 Capsule (0.16 m²) Opticap XL5 Capsule (0.28 m²) 4-inch Cartridge (0.28 m²)	KWSSA02TT3 KWSSA04TT3 KWSSA05TT1 CWSSM4S03	Opticap XL10 Capsule (0.7 m ²) Opticap XL110 Capsule (0.7 m ²) 10-inch Cartridge (0.7 m ²) Opticap XLT20 Capsule (1.4 m ²) 20-inch Cartridge (1.4 m ²) Opticap XLT30 Capsule (2.1 m ²) 30-inch Cartridge (2.1 m ²)	KWSSA10TT1 KWSSA1TTT1 CWSS71S03 KWSSA2TTT1 CWSS72S03 KWSSA3TTT1 CWSS73S03
Grade SC (1.2 µm + 0.5 µm)	Opticap XL2 Capsule (0.07 m²) Opticap XL4 Capsule (0.16 m²) Opticap XL5 Capsule (0.28 m²) 4-inch Cartridge (0.28 m²)	KWSCA02TT3 KWSCA04TT3 KWSCA05TT1 CWSCM4S03	Opticap XL10 Capsule (0.7 m ²) Opticap XLT10 Capsule (0.7 m ²) 10-inch Cartridge (0.7 m ²) Opticap XLT20 Capsule (1.4 m ²) 20-inch Cartridge (1.4 m ²) Opticap XLT30 Capsule (2.1 m ²) 30-inch Cartridge (2.1 m ²)	KWSCA10TT1 KWSCA1TTT1 CWSC71S03 KWSCA2TTT1 CWSC72S03 KWSCA3TTT1 CWSC73S03
Double-layer Polysep II Filters Grade W3 (1.0 µm + 0.2 µm)	Opticap XL2 Capsule (0.06 m²) Opticap XL4 Capsule (0.11 m²) Opticap XL5 Capsule (0.19 m²) 4-inch Cartridge (0.19 m²)	KGW3A02TT3 KGW3A04TT3 KGW3A05TT1 CGW3M4S03	Opticap XL10 Capsule (0.46 m ²) Opticap XL110 Capsule (0.46 m ²) 10-inch Cartridge (0.46 m ²) Opticap XLT20 Capsule (0.92 m ²) 20-inch Cartridge (0.92 m ²) Opticap XLT30 Capsule (1.38 m ²) 30-inch Cartridge (1.38 m ²)	KGW3A10TT KGW3A1TTT1 CGW371503 KGW3A2TTT1 CGW372503 KGW3A3TTT1 CGW373503
trafiltration/Diafiltration				
Pellicon Cassettes Biomax 10 kD membrane	A Screen Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2B010A01 P2B010A05	A Screen Maxi Cassette (2.5 m²)	P2B010A25
Biomax 30 kD membrane	A Screen Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2B030A01 P2B030A05	A Screen Maxi Cassette (2.5 m²)	P2B030A25
Biomax 50 kD membrane	A Screen Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2B050A01 P2B050A05	A Screen Maxi Cassette (2.5 m²)	P2B050A25
Ultracel PLC 10 kD membrane	C Screen Mini Cassette (0,1 m²) Cassette (0,5 m²)	P2C010C01 P2C010C05	C Screen Maxi Cassette (2.5 m²)	P2C010C25
Ultracel PLC 30 kD membrane	C Screen Mini Cassette (0.1 m²) Cassette (0.5 m²)	P2C030C01 P2C030C05	C Screen Maxi Cassette (2.5 m²)	P2C030C25

*Millistak+ DE Filters are available in a range of sizes and diameters. Contact Millipore for more details.

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

ORE SEALING STORESTED IN EAST FERRINGS

Filter Quick Reference Guide continued

Media/Membrane	Small-Scale Proces Device (area/filter)	s ing Catalogue No.	Large-Scale Proces Device (area/filter)	sing Catalogue No
/iral Clearance				
Viresolve NFP Filters	4-inch Opticap (0.077 m ²) Opticap XL10 Capsule (0.48 m ²) Opticap XLT10 Capsule (0.48 m ²) 10-inch Cartridge (0.48 m ²) Opticap XLT20 Capsule (0.97 m ²) <i>Millipore suggests using multiple cartu</i>	KVPVO4TT3 KVPVA10TT1 KVPVA1TTT1 CVPV71TP1 KVPVA2TTT1 ridges or capsules fo	Opticap XLT30 Capsule (1.45 m ²) 20-inch Cartridge (0.97 m ²) 30-inch Cartridge (1.45 m ²) or volumes > 750 L.	KVPVA3TTT1 CVPV72TP1 CVPV73TP1
Viresolve Prefilter*	Opticap (850 cm²)	KSPV01FF1	Opticap (850 cm²)	KSPV01FF1
Viresolve NFR Filters	4-inch Opticap Capsule (0.093 m²)		Opticap XL10 Capsule (0.54 m ²) Opticap XLT10 Capsule (0.54 m ²) 10-inch Cartridge (0.54 m ²) Opticap XLT20 Capsule (0.86 m ²) 20-inch Cartridge (0.86 m ²) Opticap XLT30 Capsule (1.29 m ²) 30-inch Cartridge (1.29 m ²)	KZRVA10TT1 KZRVA1TTT1 CZRV71TP1 KZRVA2TTT1 CZRV72TP1 KZRVA3TTT1 CZRV73TP1
	Millipore suggests using multiple cart	idges or capsules to	or values >3,600 L.	
terilizing-grade Filtration				
Durapore 0.22 µm Filters	Opticap XL2 Capsule (0.09 m²) Opticap XL4 Capsule (0.19 m²) Opticap XL5 Capsule (0.35 m²) 5-inch Cartridge (0.35 m²)	kvglao2tt3 kvglao4tt3 kvglao5tt1 cvgl75S01	Opticap XL10 Capsule (0.69 m ²) Opticap XLT10 Capsule (0.69 m ²) Opticap XLT20 Capsule (1.4 m ²) Opticap XLT30 Capsule (2.1 m ²) 10-inch Cartridge (0.69 m ²) 20-inch Cartridge (1.4 m ²) 30-inch Cartridge (2.1 m ²)	KVGLA10TT1 KVGLA1TTT1 KVGLA2TTT1 KVGLA3TTT1 CVGL71TP3 CVGL72TP3 CVGL73TP3
Millipore Express SHF 0.2 µm Filters	Opticap XL3 Capsule (0.16 m²) Opticap XL5 Capsule (0.29 m²) 5-inch Cartridge (0.29 m²)	KGEPA03TT3 KGEPA05TT1 CGEP75TP3	Opticap XL10 Capsule (0.54 m ²) Opticap XLT10 Capsule (0.54 m ²) Opticap XLT20 Capsule (1.08 m ²) Opticap XLT30 Capsule (1.62 m ²) 10-inch Cartridge (0.54 m ²) 20-inch Cartridge (1.08 m ²) 30-inch Cartridge (1.62 m ²)	KGEPA10TT1 KGEPA1TTT1 KGEPA2TTT1 KGEPA3TTT1 CGEP71TP3 CGEP72TP3 CGEP73TP3
Millipore Express SHC 0.5 µm + 0.2 µm PES Filters	Opticap XL3 Capsule (0.13 m²) Opticap XL5 Capsule (0.24 m²) 5-inch Cartridge (0.24 m²)	KHGEA03TT3 KHGEA05TT1 CHGE75TS3	Opticap XL10 Capsule (0.49 m ²) Opticap XLT10 Capsule (0.49 m ²) Opticap XLT20 Capsule (0.98 m ²) Opticap XLT30 Capsule (1.47 m ²) 10-inch Cartridge (0.49 m ²) 20-inch Cartridge (0.98 m ²) 30-inch Cartridge (1.47 m ²)	KHGEA10TT1 KHGEA1TTT1 KHGEA2TTT1 KHGEA3TTT1 CGEP71TS3 CGEP72TS3 CGEP73TS3

*Viresolve Prefilter will be available in Millipore's Pod technology late 2005.

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Millipore offers a comprehensive line of chromatography columns, systems and media. Contact Millipore for details.

Vaccines


Vaccines are biologically active products designed to stimulate the immune system against future invasion of a pathogen by inducing memory to specific antigens. Vaccines may be produced from viral pathogens such as those causing polio, influenza and Lyme Disease, or from bacterial pathogens such as pertussis, tetanus, diphtheria and anthrax. Recombinant fermentation techniques such as those used for hepatitis vaccine, produce highly purified antigen-specific subunits that stimulate immunity without concern of pathogen infection. Vaccine production typically uses several filtration and purification steps. To obtain a purified vaccine the selected microorganism must first be grown then the selected antigen must be separated, purified, formulated and sterilized prior to delivery.

Application Requirements

- Vaccine broths have moderate to high solids concentrations that require effective removal before downstream purification. Millipore products are designed for high yield, throughput and efficiency
- Highly purified vaccines are often required to minimize adverse reaction.
- Injectable vaccines require sterilization.

Vaccines Batch Volumes	
Mammalian Cell<2,000 L	45
Viral Vectors	48
Plasmid DNA	50
Conjugates	52
Polysaccharides	54
Filter Quick Reference Guide	56

Vaccines: Mammalian Cell



Understanding the **Options**


Essential Process Requirements	Recommended Filter	Filter Characteristics
Cell Harvesting		
 (In place of TFF/Centrifuge, post fermentation) Remove heavy solid loads from bioreactor fluid and recover product in filtrate Requires high capacity Wide feed stream variability depending on cell culture type and conditions If solid content is too high, centrifugation becomes preferred technology 	Prostak Open-Channel Modules with Durapore 0.22 µm Membrane	 Best suited for large bioreactors >1,000 L or bioreactors with high usage rates of more than 10 batches/year Open-channel design accommodates fluids containing low to mediu density and solids High flux at low transmembrane pressure Robust construction allows multiple use Validated for multiple SIP cycles Although Durapore 0.22 µm membrane is typical for this application Prostak Modules are available in with a wide range of membranes t accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.
	Double-layer Millistak+ HC Filters (Grade D0HC or C0HC)	 For bioreactor volumes up to 1,000 L or larger volumes with low use rates of less than 10 batches/year Double layer design enhances loading capacity and filtrate quality Unique configuration allows compression of multiple process steps in and lower and filtrate quality
		 one, lowering overall filtration costs Selection of COHC or DOHC media grade depends on particle size distribution and feed solution. Choice should be based upon small- scale testing.
•	ALTERNATIVE: For smaller batch sizes wh Double-layer Milligard 0.5 μm + 0.2 μm	 Selection of COHC or DOHC media grade depends on particle size distribution and feed solution. Choice should be based upon small- scale testing.
 (Post TFF or Centrifuge) Remove cell debris, small particles and colloids passed through the primary clarification step Potential for variations in fluid particle size distribution 	ALTERNATIVE: For smaller batch sizes wh Double-layer Milligard 0.5 µm + 0.2 µm Triple-layer Millistak+ HC Filters (Grade B1HC)	 Selection of COHC or DOHC media grade depends on particle size distribution and feed solution. Choice should be based upon small-scale testing. ere no centrifuge or TFF step is required Millipore suggests using Clarigard 0.3 µm (Grade SS) Filters in your process. Choice should be based on small-scale testing. Ideal solution post-centrifuge for medium and small volume bioreacte with <2,000 L volume Triple-layer configuration includes a membrane bottom layer to enha filter loading capacity and retention High filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step
 primary clarification step Potential for variations in fluid particle size distribution Must have high capacity and protect downstream sterilizing- 	Double-layer Milligard 0.5 µm + 0.2 µm Triple-layer Millistak+ HC Filters (Grade B1HC)	 Selection of COHC or DOHC media grade depends on particle size distribution and feed solution. Choice should be based upon small-scale testing. ere no centrifuge or TFF step is required Millipore suggests using Clarigard 0.3 µm (Grade SS) Filters in your process. Choice should be based on small-scale testing. Ideal solution post-centrifuge for medium and small volume bioreacte with <2,000 L volume Triple-layer configuration includes a membrane bottom layer to enha filter loading capacity and retention High filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Unique design enables the compression of multiple process steps into

Essential Process Requirements	Recommended Filter	Filter Characteristics
 Bioburden Reduction Reduces bioburden at intermediate process step Protects downstream filters, media and equipment Preserves product purity Sterilizing-grade filtration required 	Double-layer Millipore Express SHC 0.5 µm + 0.2 µm Filters	 Sterilizing-grade PES 0.2 µm membrane with an additional 0.5 µm prefilter layer all in one pleated device Designed for bulk intermediate processing where fluids may be fouling in batch sizes ranging from 100 to 20,000 L. PES membrane provides broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates at low pressure drop Can be integrity tested on-site
 Concentration and Diafiltration (Prior to column chromatography steps) Concentration of process fluids and buffer exchange Will extend the life of expensive chromatography media and improve their speed and efficiency Fast, robust process able to accommodate feed fluid variations Wide chemical compatibility with cleaning agents Easily scalable from lab to manufacturing scale 	Pellicon C Screen Cassettes with Ultracel PLC 100, 300 or 1,000 kD Membrane	 Low feed flow requirements minimize pumping, working and hold up volumes Highly retentive regenerated cellulose membranes offer good permeate flux and withstand process upsets Robust low binding void-free Ultracel PLC membranes assure consistent processing from batch to batch, have good chemical compatibility and are easy to clean Complete range of devices for easy scale-up Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing.
 Concentration and Diafiltration (For final formulation) Concentration and diafiltration adjusts the end product to the prop- er dosage conditions prior to final packaging Fast, robust process able to accom- modate feed fluid variations Easily scalable from lab to manufac- turing scale 	Pellicon C Screen Cassettes with Ultracel PLC 100 or 300 kD Membrane	 Low feed flow requirements minimize pumping, working and hold up volumes Higher product recovery and flux Highly retentive regenerated cellulose membranes offer good permeate flux and withstand process upsets Robust low binding void-free Ultracel PLC membranes assure consistent processing from batch to batch, have good chemical compatibility and are easy to clean Complete range of devices for easy scale-up Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing.
 Sterile Filtration Sterilizing-grade step to reduce bioburden or sterilize heat labile products Highly validated and reliable technology Preserves product purity Ensures product safety 	3 Durapore 0.22 μm Filters	 Low protein-binding sterilizing-grade PVDF membrane Low extractables preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing and thousands of applications assure proven performance Validated for multiple SIP and hot water sanitization cycles Available in Millipak stacked disc format which allows minimal hold-up volume Although 0.22 µm membrane is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user. Choice should be based on small-scale testing.

For details on Tank Venting (9), see page 70.

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289 Vaccines: Mammalian Cell

Vaccines: Viral Vectors





Understanding the **Options**

Essential Process Requirements	Recommended Filter	Filter Characteristics
Virus Barrier		
 Removes adventitious viruses Ensures product safety Requires a highly validated and reliable technology Maximizes product recovery Preserves and ensures product purity 	2 Viresolve NFP Filters1	 >4 log removal of parvovirus and other small viruses without compromising flow rate or removing vital media nutrients Robust PVDF membrane >98% protein recovery up to 160 kD Available in multiple formats for easy scale-up and scale-down 100% Integrity testing assures performance Can be integrity tested on-site To ensure performance and capacity, Millipore suggests using in series with the Viresolve Prefilter 1.
Clarification		
 Removes cell debris, small particles and colloids after the cell lysis step Must have high throughput capacity Protects downstream sterilizing- grade membrane filters 	 3 Single-layer Millistak+ CE Filters (Grade 40CE, 45CE, or 50CE) 	 Better suited for volumes <2,000 L High internal surface area for maximum particle capture loading Filter matrix exhibits positive charge properties to enhance filtration High porosity provides low pressure drop Available in several media grades to accommodate the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing.


48

Essential Process Requirements	Recommended Filter	Filter Characteristics
 Bioburden Reduction Reduces bioburden Protects downstream chromatography and UF/DF steps Preserves product purity 	Double-layer Durapore 0.45 µm Filters (with 0.5 µm prefilter laye	 Low protein-binding PVDF membrane with prefilter layer Highly retentive membrane reduces bioburden Low extractables and non-fiber releasing PVDF chemistry preserves product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing and thousands of applications assures proven performance Validated for multiple SIP and hot water sanitization cycles
 Concentration and Diafiltration (Prior to column chromatography steps Concentration of process fluids and buffer exchange Will extend the life of expensive chromatography media and improve their speed and efficiency Fast, robust process able to accommodate feed fluid variations Wide chemical compatibility with cleaning agents Easily scalable from lab to manufacturing scale 	5 Pellicon V Screen Cassetti with Ultracel PLC 300 kD Membrane	
 Concentration and Diafiltration (For final formulation) Concentration and diafiltration adjusts the end product to the proper dosage conditions prior to final packaging Fast, robust process able to accommodate feed fluid variations Easily scalable from lab to manufacturing scale 	6 Pellicon C Screen Cassett with Ultracel PLC 300 kD Membrane	
 Sterile Filtration Sterilizing-grade step reduces bioburden Highly validated and reliable technology Preserves and ensures product purity Ensures product safety 	7 Durapore 0.22 μm Filters	 Low protein-binding sterilizing-grade PVDF membrane Low extractables preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing and thousands of applications assure proven performance Validated for multiple SIP and hot water sanitization cycles Available in Millipak stacked disc format which allows minimal hold-up volume Although 0.22 µm membrane is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multi-layer configurations to accommodate the needs of each user. Choice should be based on small-scale testing.

For details on Tank Venting (8), see page 70.

Vaccines: Viral Vectors

Vaccines: Plasmid DNA



Understanding the **Options**

Essential Process Requirements	Recommended Filter	Filter Characteristics
Clarification and Solids Removal		
 (In place of bag filter) Remove solids after the cell lysis step Have high debris holding capacity Protect downstream membranes Charged medias should be avoided due to plasmid interaction Typically operated at low delta P to minimize precipitate or breakthrough Process is more efficient in cases of flocculants that float Washing of precipitate to reduce endotoxin and genomic DNA contaminants 	Polygard CR 10 µm Filters	 For use in place of a bag filter or for extra clarification after cell lysis Multi-stage graded density design retains solids or sediment within the depth matrix Polypropylene media provides excellent solids capacity and high throughput.
	2 Clarigard 0.5 µm Filters	 For use in series after the Polygard CR filter when no bag filter is used for solids removal Polypropylene graded density prefilter for robust particle and colloid removal 1-2 log bioburden reduction Validated for multiple sanitization and SIP cycles Higher filtrate quality allows smaller size requirements for downstream sterilizing-grade filtration step Non-fiber releasing structure preserves product purity.

Essential Process Requirements

Concentration and Diafiltration

- (Prior to column chromatography steps)
- Concentration of process fluids and buffer exchange
- Will extend the life of expensive chromatography media and improve their speed and efficiency
- Fast, robust process able to accommodate feed fluid variations
- Wide chemical compatibility with cleaning agents
- Easily scalable from lab to manufacturing scale

Concentration and Diafiltration

- (For final formulation)
- Concentration and diafiltration adjusts the end product to the proper dosage conditions prior to final packaging
- Fast, robust process able to accommodate feed fluid variations
- Easily scalable from lab to manufacturing scale

Pellicon V Screen Cassettes

with Ultracel PLC 30 or

100 kD Membrane

Recommended Filter

- 4 Pellicon C Screen Cassettes with Ultracel PLC 30 or 100 kD Membranes
- Low feed flow requirement minimizes pumping, working and hold up volumes

• Low feed flow requirement minimizes pumping, working and hold up

• Highly retentive regenerated cellulose membranes offer good permeate

• Robust low binding void-free Ultracel PLC membranes assure consistent

• Choose a membrane molecular weight cut-off 3-5X smaller than the

biomolecule. Choice should be based on small-scale testing.

processing from batch to batch, have good chemical compatibility and

• Higher product recovery and flux

flux and withstand process upsets

Complete range of devices for easy scale-up

Filter Characteristics

are easy to clean

volumes

- Highly retentive regenerated cellulose membranes offer good permeate flux and withstand process upsets
- Robust low binding void-free Ultracel PLC membranes assure consistent processing from batch to batch, have good chemical compatibility and are easy to clean
- Complete range of devices for easy scale-up
- Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing.

ALTERNATIVE: In case of high concentrations (>5 g/L) Pellicon V Screen cassettes are recommended.

Sterile Filtration

- Sterilizing-grade step removes bacteria prior to aseptic fill
- Ensures product safety
- Highly validated and reliable technology
- Preserves product purity

NOTE: Membrane chemistries other than PES are known to cause gel formation at the membrane surface. We strongly recommend a PES filter for this step.




- Sterilizing-grade PES 0.2 µm membrane with an additional 0.5 µm PES prefilter layer all in one pleated device
- Double-layer construction provides excellent capacity even in high salt conditions
- PES membrane provides broad chemical compatibility across a wide pH range (1–14)
- Robust construction validated for multiple SIP cycles
- 100% integrity tested to ensure quality
- Asymmetric PES pore structure delivers' extremely high flow rates at low pressure drop
- Can be integrity tested on-site

For details on Tank Venting 6, see page 70.

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289



Vaccines: Conjugates





Understanding the **Options**

Recommended Filter	Filter Characteristics
Pellicon C Screen Cassettes with Ultracel PLC 100, 300 or 1,000 kD Membranes	 Low feed flow requirement minimizes pumping, working and hold up volumes. Higher product recovery and flux Highly retentive regenerated cellulose membranes offer good permeat flux and withstand process upsets Robust low binding void-free Ultracel PLC membranes assure consisten processing from batch to batch, have good chemical compatibility an are easy to clean Complete range of devices for easy scale-up
2 Double-layer Multilayer Durapore 0.45 µm + 0.22 µm Filters	 Sterilizing-grade PVDF 0.22 µm membrane with an additional 0.45 µm prefilter layer all in one pleated device Low-binding membranes assure product yield and sterility 100% Integrity testing ensures quality Double-layer construction provides excellent capacity and protection of downstream equipment Can be integrity tested on-site
	 Pellicon C Screen Cassettes with Ultracel PLC 100, 300 or 1,000 kD Membranes Double-layer Multilayer Durapore 0.45 µm +

Pellicon

10

MILLID


52

Essential Process Requirements	Recommended Filter	Filter Characteristics
Concentration and Diafiltration		
 (Prior to column chromatography steps) Concentration of process fluids and buffer exchange Will extend the life of expensive chromatography media and improve their speed and efficiency Fast, robust process able to accommodate feed fluid variations Wide chemical compatibility with cleaning agents Easily scalable from lab to manufacturing scale 	3 Pellicon V Screen Cassettes with Ultracel PLC 30, 100, 300 or 1,000 kD Membranes	 Low feed flow requirement minimizes pumping, working and hold up volumes Highly retentive regenerated cellulose membranes offer good permeate flux and withstand process upsets Robust low binding void-free Ultracel PLC membranes assure consistent processing from batch to batch, have good chemical compatibility and are easy to clean Complete range of devices for easy scale-up Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing.
	ALTERNATIVE: For applications where c Ultracel membrane.	organic solvents are used, Millipore suggests utilizing a Prostak UF Module with
 Sterile Filtration Sterilizing-grade step reduces bioburden Highly validated and reliable technology Preserves product purity Ensures product safety 	Δurapore 0.22 µm Filters	 Low protein-binding sterilizing-grade PVDF membrane Low extractables preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing and thousands of applications assure proven performance Validated for multiple SIP and hot water sanitization cycles Available in Millipak stacked disc format which allows minimal hold-up volume Although 0.22 µm membrane is typical for this application, Durapore filters are available in several pore sizes and, in single-layer or multi-layer configurations to accommodate the needs of each user. Choice should be based on small-scale testing.

For details on Tank Venting (5), see page 70.



Vaccines: Polysaccharides



• Remove whole cells and solids from
bioreactor fluid and recover product
in filtrate
 Requires high capacity

- Wide feed stream variability depending on cell culture type and conditions
- If solid content is too high, centrifugation becomes preferred technology
- Membrane selection will depend upon the size of the polysaccharide

Secondary Clarification

- Cell recovery from the fermenter broth, elimination of waste fluid in the filtrate
- High solids content in feed stream
- Feed stream quality can vary depending on cell type and culture conditions

Prostak Open-Channel Modules with Durapore 0.22, 0.45 or 0.65 µm Membrane

Triple-layer Millistak+ HC Filters

(Grade B1HC)

• Triple-layer configuration includes a membrane bottom layer to enhance filter loading capacity and retention

• Best suited for large bioreactors >1,000 L or more than

High flux at low transmembrane pressureAllows volume reduction as fluid is concentrated

• Robust construction enables multiple use

Validated for multiple SIP cycles

• Open-channel design to accommodate high cell density and high solids

• Selection of Durapore membrane depends on particle size distribution

in feed solution. Choice should be based upon small-scale testing.

10 batches/year

cell culture fluids

• Unique design enables the compression of multiple steps to one, lowering overall filtration costs.

Essential Process Requirements	Recommended Filter	Filter Characteristics
 Bioburden Reduction Reduces bioburden at intermediate process step to reduce the risk of pyrogenic contamination and damage Protects downstream filters, media and equipment Preserves product purity Sterilizing-grade filtration required 	Millipore Express SHC 0.5 µm + 0.2 µm Filters	 Sterilizing-grade PES 0.2 µm membrane with an additional 0.5 µm prefilter layer all in one pleated device may eliminate the need for a prefilter Designed for bulk intermediate processing where fluids may be fouling in batch sizes ranging from 100 to 20,000 L. PES membrane provides broad chemical compatibility across a wide pH range (1–14) Robust construction validated for multiple SIP cycles 100% integrity tested to ensure quality Asymmetric pore structure delivers extremely high flow rates at low
	ALTERNATIVE: If a PVDF or low-protein + 0.22 µm in your small-scale trials.	 Asymmetric pole structure derivers extremely high now rates at row pressure drop Can be integrity tested on-site binding membrane is required, Millipore suggests testing Multilayer Durapore 0.45 µm
Concentration and Diafiltration		
 (For final formulation) Concentration and diafiltration adjusts the end product to the prop- er dosage conditions prior to final packaging Fast, robust process able to accommodate feed fluid variations Easily scalable from lab to manufacturing scale 	4 Pellicon C Screen Cassettes with Ultracel PLC 30 or 100 kD Membranes	 Low feed flow requirement minimizes pumping, working and hold up volumes Higher product recovery and flux Highly retentive regenerated cellulose membranes offer good permeate flux and withstand process upsets Robust low binding void-free Ultracel PLC membranes assure consistent processing from batch to batch, have good chemical compatibility and are easy to clean Complete range of devices for easy scale-up Choose a membrane molecular weight cut-off 3–5X smaller than the biomolecule. Choice should be based on small-scale testing.
 Prefiltration (Bulk intermediate) Removes colloidal and particulate contaminants and extend the life of final filters Should preserve polysaccharide purity and operate consistently at high differential pressures and flow rates Must be able to withstand multiple SIP or hot water sanitization cycles Run efficiently to ensure process economics 	5 Double-layer Milligard Filters (Grade LS, 0.5 μm + 0.2 μm)	 Double-layer pleated configuration of mixed esters of cellulose
	ALTERNATIVE: When choosing Multilay The prefilter layer is built into the final f	yer Durapore 0.45 μm + 0.22 μm for Final Filtration, this step is not required. ilter.

Vaccines: Polysaccharides

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Understanding the **Options** continued

Essential Process Requirements	Recommended Filter	Filter Characteristics
Final Sterile Filtration		
 Sterilizing-grade step reduces bioburden Highly validated and reliable technology Preserves product purity Ensures product safety 	Single-layer Durapore 0.22 μm Filters	 Use in series with Milligard LS Filters Low protein-binding sterilizing-grade PVDF membrane Low extractables preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing and thousands of applications assures proven performance Validated for multiple SIP and hot water sanitization cycles Available in Millipak stacked disc format which allows minimal hold-up volume Although 0.22 µm membrane is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multilayer configurations to accommodate the needs of each user. Choice should be based on small-scale testing.
	 Double-layer Durapore Multilayer 0.45 μm + 0.22 μm Filters 	 Low protein-binding sterilizing-grade PVDF 0.22 µm membrane layer combined with a 0.5 µm prefilter layer Very low extractables preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity testing and thousands of applications assure proven performance Validated for multiple SIP and hot water sanitization cycles Prefiltration step 3 not required with this choice.

For details on Tank Venting 🕖, see page 70.



Filter Quick Reference Guide

Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
Mammalian Cell		
Prostak MF Open-Channel 2-stack Modules		
Durapore 0.22 µm membrane	0.17 m ²	PSGVAG021
Millistak+ Mini Capsules		
Grade B1HC Grade C0HC Grade D0HC	23 cm ²	MB1HC23HH3 MC0HC23HH3 MD0HC23HH3
Opticap XL1 Capsules		
Clarigard 0.3 µm media	1-inch*	K003A51TT1
OptiScale Capsules		
Double-layer Milligard SS 0.5 µm + 0.2 µm membrane Durapore 0.22 µm membrane Double-layer Millipore Express SHC 0.5 µm + 0.2 µm membrane	13.8 cm ²	SVSSA47FF3 SVGLA47FF3 SHGEA47FF3
Pellicon 2 C Screen Mini-Cassettes		
Ultracel PLC C Screen 100 kD membrane Ultracel PLC C Screen 300 kD membrane Ultracel PLC C Screen 1,000 kD membrane	0.1 m ²	P2C100C01 P2C300C01 P2C01MC01
*Filter element size		

Filter Format	Area/Filter	Catalogue No.
/iral Vectors		
Millistak+ Mini Devices		
Grade CE40	002	M40CE23HH3
Grade CE45 Grade CE50	23 cm ²	M45CE23HH3 M50CE23HH3
		1000CE23003
Evaluation Kit with OptiScale-25 Capsules**	0.5.0	
Viresolve NFP membrane	3.5 cm ²	SVPVA25NB9
OptiScale-40 Devices		
Viresolve Prefilter	5 cm ²	SSPVA40NB9
OptiScale Capsules		
Durapore 0.22 µm membrane	13.8 cm ²	SVGLA47FF3
Durapore 0.45 µm membrane (order with 0.5 µm prefilter SW06A47FF3)	10.0 cm	SVHLA47FF3
		01110 (4) 110
Pellicon 2 V Screen Mini-Cassettes	0.1 2	000000000
Ultracel PLC 300 kD membrane	0.1 m ²	P2C300V01
Plasmid DNA		
Opticap XL1 Capsules		
Polygard CR 10 µm media	1-inch*	KR10A51TT1
Clarigard 0.5 µm media	I -INCN "	K005A51TT1
DptiScale Capsules		
Double-layer Millipore Express SHC membrane	13.8 cm ²	SHGEA47FF3
	10.0 011	011027177170
Pellicon 2 V Screen Mini-Cassettes		
Ultracel PLC 30 kD membrane Ultracel PLC 100 kD membrane	0.1 m ²	P2C030V01 P2C100V01
		120100/01
Pellicon 2 C Screen Mini-Cassettes		
Ultracel PLC 30 kD membrane	0.1 m ²	P2C030C01
Ultracel PLC 100 kD membrane		P2C100C01
Conjugates		
Pellicon V Screen Mini-Cassettes		
Ultracel PLC 30 kD membrane		P2C030V01
Ultracel PLC 100 kD membrane	0.1 m ²	P2C100V01
Ultracel PLC 300 kD membrane	0.1 11	P2C300V01
Ultracel PLC 1,000 kD membrane		P2C01MV01
Pellicon C Screen Mini-Cassettes		
Ultracel PLC 30 kD membrane		P2C030C01
Ultracel PLC 100 kD membrane	0.1 m ²	P2C100C01
Ultracel PLC 300 kD membrane	0.1 m²	P2C300C01
Ultracel PLC 1,000 kD membrane		P2C01MC01
Prostak UF 4-stack Modules		
Ultracel PL 5 kD membrane		PSLCSP041
Ultracel PL 10 kD membrane	0.39 m ²	PSLGSP041
Ultracel PL 30 kD membrane		PSLTSPO41
OptiScale Devices		
Durapore 0.22 µm membrane		SVGLA47FF3
Multilayer Durapore 0.45 µm + 0.22 µm membrane	13.8 cm ²	SHGLA47FF3
		01100 (4) 110
Polysaccharides		
Prostak MF Open-Channel 2-stack Modules		
Durapore 0.22 µm membrane	0.17 2	PSGVAG021
Durapore 0.45 µm membrane	0.17 m ²	PSHVAG021
Durapore 0.65 µm membrane		PSDVAG021
OptiScale Devices		
Double-layer Milligard LS 0.5 µm + 0.2 µm media		SWLSA47FF3
Double-layer Millipore Express SHC membrane	13.8 cm ²	SHGEA47FF3
Durapore 0.22 µm membrane		SVGLA47FF3
Multilayer Durapore 0.45 µm + 0.22 µm membrane		SHGLA47FF3
Pellicon 2 C Screen Mini-Cassettes		
Ultracel PLC 30 kD membrane	0.1 m ²	P2C030C01
Ultracel PLC 100 kD membrane	0.1 11-	P2C100C01
Aillistak+ Mini-Capsules		
Grade B1HC	23 cm ²	MB1HC23HH3
	22.011	
*Filter element size		
*Viresolve membranes are available in an Evaluation Kit containing 9 OptiScale-25 C	Canada 2 10	mampiana lata a l

Lenntech

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Recommended Filters

Prostak MF Open-Channel Moo	Area/Filter	0.22 μm	0.45 µm	0.65 µm	
2-stack	0.17 m ²	PSGVAG021	PSHVAG021	PSDVAG021	
4-stack	0.33 m ²	PSGVAG041	PSHVAG041	PSDVAG041	
10-stack	0.84 m ²	PSGVAG101	PSHVAG101	PSDVAG101	
20-stack	1.7 m ²	SK2P484EO	SK2P242E9	SK2P446E0	
Pellicon 2 C Screen Cassettes v	vith Ultracel PLC Membrane	•			
	Area/Filter	30 kD	100 kD	300 kD	1,000 kD
Mini-cassette	0.1 m ²	P2C030C01	P2C100C01	P2C300C01	P2C01MC01
Cassette	0.5 m ²	P2C030C05	P2C100C05	P2C300C05	P2C01MC05
Maxi-cassette	2.5 m ²	P2C030C25	P2C100C25	P2C300C25	P2C01MC25
Pellicon 2 V Screen Cassettes w			_	_	
	Area/Filter	30 kD	100 kD	300 kD	1,000 kD
Mini-cassette	0.1 m ²	P2C030V01	P2C100V01	P2C300V01	P2C01MV01
Cassette	0.5 m ²	P2C030V05	P2C100V05	P2C300V05	P2C01MV05
Maxi-cassette	2.0 m ²	P2C030V20	P2C100V20	P2C300V20	P2C01MV20
Millistak+ HC Filters	Area/Filter	Grade B1HC	Grade COHC	Area/Filter	Grade DOHC
1-cell Pod	0.1 m ²	MB1HC01FS1	MC0HC01FS1	0.1 m ²	MD0HC01FS
5-cell Pod	0.5 m ²	MB1HC05FS1	MC0HC05FS1	0.5 m ²	MD0HC05FS
10-cell Pod	1.0 m ²	MB1HC10FS1	MCOHC10FS1	1.0 m ²	MD0HC10FS
Opticap Capsule	650 cm ²	KB1HC10FF1	KCOHC10FF1	650 cm ²	KD0HC10FF1
2-cell Stack, 16-inch dia.	0.45 m ²	LB1HCH6S6	LCOHCH6S6	0.45 m ²	LDOHCH6S6
8-cell Stack, 16-inch dia.	1.8 m ²	LB1HCG6S2	LCOHCG6S2	1.6 m ²	LDOHCG6S2*
Villistak+ CE Filters	Area/Filter	Grade 40CE	Grade 45CE	Grade 50CE	
Opticap Capsule	930 cm ²	K40CE10FF1	K45CE10FF1	K50CE10FF1	
6-cell Stack, 12-inch dia.	0.63 m ²	L40CEF2S3	L45CEF2S3	L50CEF2S3	
9-cell Stack, 12-inch dia.	0.03 m ²	L40CE/253	L45CEJ2S3	L50CE/253	
	1.37 m ²	-	-	-	
13-cell Stack, 12-inch dia.		L40CEN2S2	L45CEN2S2	L50CEN2S2	
16-cell Stack, 12-inch dia.	1.68 m ² 3.47 m ²	L40CER2S2	L45CER2S2	L50CER2S2	
16-cell Stack, 16-inch dia.	3.4/ m²	L40CET6S1	L45CET6S1	L50CET6S1	
Clarigard Filters	Filter Element Size	0.3 µm	0.5 µm		
Opticap XL1 Capsule	1-inch	K003A51TT1	K005A51TT1		
2-inch Cartridge	2-inch	D003N0S03	D005N0S03		
Opticap XL5 Capsule	5-inch	KOO3AO5TT1	K005A05TT1		
Opticap XL10 Capsule	10-inch	KOO3A1OTT1	KOO5A1OTT1		
10-inch Cartridge	10-inch	D00371S01	D00571S01		
20-inch Cartridge	20-inch	D00372S01	D00572S01		
30-inch Cartridge	30-inch	D00373S01	D00573S01		
40-inch Cartridge	40-inch	D00374S01	D00574S01		
Polygard CR Filters	Filter Element Size	10 µm			
Opticap XL1 Capsule	1-inch	KR10A51TT1			
2-inch Cartridge	2-inch	CR10M0203			
Opticap XL5 Capsule	5-inch	KR10A05TT1			
Opticap XL10 Capsule	10-inch	KR10A10TT1			
10-inch Cartridge	10-inch	CR1071006			
20-inch Cartridge	20-inch	CR1072006			
30-inch Cartridge	30-inch	CR1073006			
40-inch Cartridge	40-inch	CR1074006			
Milligard Filters	Area/Filter	Grade SS	Grade LS		
Opticap XL2 Capsule	0.07 m ²	KWSSA02TT3	KWLSA02TT3		
Opticap XL4 Capsule	0.16 m ²	KWSSA04TT3	KWLSA04TT3		
4-inch Cartridge	0.28 m ²	CWSSM4S03	CWLSM4S03		
	0.28 m ²	KWSSA05TT1	KVVLSA05TT1		
Opticap XL5 Capsule		KWSSA10TT1	KVVLSA10TT1		
Opticap XL5 Capsule	0.7 m ²				
Opticap XL5 Capsule Opticap XL10 Capsule	0.7 m ² 0.7 m ²	KWSSA1TTT1	-		
Opticap XL5 Capsule Opticap XL10 Capsule Opticap XLT10 Capsule		KWSSA1TTT1 CWSS71S03	- CWLS71S03		
Opticap XL5 Capsule Opticap XL10 Capsule Opticap XLT10 Capsule 10-inch Cartridge	$0.7 \ m^2$	CWSS71S03	CWLS71S03		
Opticap XL5 Capsule Opticap XL10 Capsule Opticap XLT10 Capsule 10-inch Cartridge Opticap XLT20 Capsule	0.7 m ² 0.7 m ² 1.4 m ²	CWSS71S03 KWSSA2TTT1	-		
Opticap XL5 Capsule Opticap XL10 Capsule Opticap XL110 Capsule 10-inch Cartridge Opticap XLT20 Capsule 20-inch Cartridge	0.7 m ² 0.7 m ² 1.4 m ² 1.4 m ²	CWSS71S03 KWSSA2TTT1 CWSS72S03	CWLS71503 CWLS72503		
Opticap XL5 Capsule Opticap XL10 Capsule Opticap XLT10 Capsule 10-inch Cartridge Opticap XLT20 Capsule	0.7 m ² 0.7 m ² 1.4 m ²	CWSS71S03 KWSSA2TTT1	-		

*Millistak+ Grade DOHC comes in 7-cell 16-inch stacks.

Viresolve NFP Filters	Area/Filter	Catalogue No.	Viresolve Prefilter	Area/Filter	Catalogue No.
4-inch Opticap Capsule	0.077 m ²	KVPVO4TT3 -	10-inch Opticap Capsule	850 cm ²	KSPV01FF1
Opticap XL10 Capsule	0.48 m ²	KVPVA10TT1	and the second second second		
Opticap XLT10 Capsule	0.48 m ²	KVPVA1TTT1			
10-inch Cartridge	0.48 m ²	CVPV71TP1			
Opticap XLT20 Capsule	0.97 m ²	KVPVA2TTT1			
20-inch Cartridge	0.97 m ²	CVPV72TP1			
Opticap XLT30 Capsule	1.45 m ²	KVPVA3TTT1			
30-inch Cartridge	1.45 m ²	CVPV73TP1			
Durapore Filters	Area/Filter	0.22 µm Sterilizing-grade	0.45 µm + 0.5 µm Prefilter Layer	Area/Filter	0.45 µm + 0.22 µm Sterilizing-grade Multilayer
Opticap XL2 Capsule	0.09 m ²	KVGLA02TT3			
Opticap XL4 Capsule	0.19 m ²	KVGLA04TT3			
5-inch Cartridge	0.35 m ²	CVGL75S01			
Opticap XL5 Capsule	0.35 m ²	KVGLA05TT1			
Opticap XL5					
Gamma-compatible Capsule	0.35 m ²	KVGLG05TT1			
Opticap XL10 Capsule	0.69 m ²	KVGLA10TT1	KVHLA10TT1	0.55 m ²	KHGLA10TT1
Opticap XL10					
Gamma-compatible Capsule	0.69 m ²	KVGLG10TT1			
10-inch Cartridge	0.69 m ²	CVGL71TP3	CVHL71TP3	0.55 m ²	CHGL71TP3
Opticap XLT10 Capsule	0.69 m ²	KVGLA1TTT1		0.55 m ²	KHGLA1TTT1
Opticap XLT10	0.07 11			0.00 m	
Gamma-compatible Capsule	0.69 m ²	KVGLG1TTT1			
20-inch Cartridge	1.4 m ²	CVGL72TP3	CVHL72TP3	1.1 m ²	CHGL72TP3
Opticap XLT20 Capsule	1.4 m ²	KVGLA2TTT1	CVIID 2110	1.2 m ²	KHGLA2TTT1
Opticap XLT20 Opticap XLT20	1.4 111	KYOLAZITTI		1.2 111	KI IOLAZI I I I
Gamma-compatible Capsule	1.4 m ²	KVGLG2TTT1			
30-inch Cartridge	2.1 m ²	CVGLZ3TP3	CVHL73TP3	1.65 m ²	CHGL73TP3
Opticap XLT30 Capsule	2.1 m ²	KVGLA3TTT1	CVIID SITS	1.75 m ²	KHGLA3TTT1
	Z.1 III	RVGLASTITI		1.7.5 m	RIGLASTIT
Opticap XLT30	2.1 m ²	K/CICOTTI			
Gamma-compatible Capsule		KVGLG3TTT1			
40-inch Cartridge	2.76 m ²	CVGL74TP3	CVHL74TP3		
Millipore Express SHC Sterilizing-gr	rade Filters	Area/Filter	0.5 µm + 0.2 µm		
Opticap XL3 Capsule		0.13 m ²	KHGEA03TT3		
Opticap XL3 Gamma-compatible	Capsule	0.13 m ²	KHGEG03TT3		
Opticap XL5 Capsule		0.23 m ²	KHGEA05TT1		
Opticap XL5 Gamma-compatible	Capsule	0.24 m ²	KHGEG05TT1		
5-inch Cartridge	[0.23 m ²	CHGE75TS3		
			KHGEA10TT1		
		0.49 m^2			
Opticap XL10 Capsule		0.49 m ² 0.49 m ²			
Opticap XL10 Capsule Opticap XLT10 Capsule		0.49 m ² 0.49 m ²	KHGEA1TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10		0.49 m ²	KHGEA1TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule					
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110		0.49 m ² 0.54 m ²	KHGEA1TTT1 KHGEG10TT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110 Gamma-compatible Capsule		0.49 m ² 0.54 m ² 0.54 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110 Gamma-compatible Capsule 10-inch Cartridge		0.49 m ² 0.54 m ² 0.54 m ² 0.49 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110 Gamma-compatible Capsule 10-inch Cartridge Opticap XL120 Capsule		0.49 m ² 0.54 m ² 0.54 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110 Gamma-compatible Capsule 10-inch Cartridge Opticap XL120 Capsule Opticap XL120		0.49 m ² 0.54 m ² 0.54 m ² 0.49 m ² 0.98 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3 KHGEA2TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110 Gamma-compatible Capsule 10-inch Cartridge Opticap XL120 Capsule Opticap XL120 Gamma-compatible Capsule		0.49 m ² 0.54 m ² 0.54 m ² 0.49 m ² 0.98 m ² 1.09 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3 KHGEA2TTT1 KHGEG2TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL110 Gamma-compatible Capsule 10-inch Cartridge Opticap XL120 Capsule Opticap XL120 Gamma-compatible Capsule 20-inch Cartridge		0.49 m ² 0.54 m ² 0.49 m ² 0.98 m ² 1.09 m ² 0.98 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3 KHGEA2TTT1 KHGEG2TTT1 CHGE72TS3		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL10 Gamma-compatible Capsule 10-inch Cartridge Opticap XLT20 Gamma-compatible Capsule 20-inch Cartridge Opticap XLT30 Capsule		0.49 m ² 0.54 m ² 0.54 m ² 0.49 m ² 0.98 m ² 1.09 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3 KHGEA2TTT1 KHGEG2TTT1		
Opticap XL10 Capsule Opticap XL10 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL10 Gamma-compatible Capsule 10-inch Cartridge Opticap XLT20 Gamma-compatible Capsule 20-inch Cartridge Opticap XLT30 Capsule Opticap XLT30		0.49 m ² 0.54 m ² 0.54 m ² 0.49 m ² 0.98 m ² 1.09 m ² 0.98 m ² 1.47 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3 KHGEA2TTT1 KHGEG2TTT1 CHGE72TS3 KHGEA3TTT1		
Opticap XL10 Capsule Opticap XL110 Capsule Opticap XL10 Gamma-compatible Capsule Opticap XL10 Gamma-compatible Capsule 10-inch Cartridge Opticap XLT20 Gamma-compatible Capsule 20-inch Cartridge Opticap XLT30 Capsule		0.49 m ² 0.54 m ² 0.49 m ² 0.98 m ² 1.09 m ² 0.98 m ²	KHGEA1TTT1 KHGEG10TT1 KHGEG1TTT1 CHGE71TS3 KHGEA2TTT1 KHGEG2TTT1 CHGE72TS3		

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Millipore offers a comprehensive line of chromatography columns, systems and media. Contact Millipore for details.

LENNTECH info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Final Aseptic Fill



configurations. Choice should be based on small-scale testing.

Final Aseptic Filling



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening for the best candidates. If capacity data illustrates that fluid is a non-plugging stream (≥1,000 L/m²) then sizing is based on flow rate and pressure drop requirements. Millipore recommends normalizing for pressure and area of the OptiScale small-scale screening and the pressure data the interval of the pressure and the interval of the optiScale screening for the screen

Millipore recommends normalizing for pressure and area of the OptiScale small-scale screening capsules. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
OptiScale Devices		
Milligard SC 1.2 µm + 0.5 µm membrane		SWSCA47FF3
Milligard SS 0.5 µm + 0.2 µm membrane		SWSSA47FF3
Milligard 1.2 µm membrane	13.8 cm ²	SW19A47FF3
Milligard 0.5 µm membrane		SW06A47FF3
Milligard 0.2 µm membrane		SW03A47FF3
OptiScale Devices		
Durapore 0.22 µm membrane		SVGLA47FF3
Millipore Express SHF 0.2 µm membrane	13.8 cm ²	SGEPA47FF3
Double-layer Millipore Express SHC 0.5 µm + 0.2 µm membrane		SHGEA47FF3

Recommended Filters

Recommendation table based on filter capacity of approximately 1,000 L/m²

Volume	Prefiltration (optional) Device (area/filter) Catalogue No.		Final Sterilizing-grade Device (area/filter)	Filtration Catalogue No.	
Solution Concentration < 10 mg/mL					
5–10 L	NOT REQUIRED		Durapore 0.22 µm Filters Millipak Gold 20 Unit (0.01 m²)	MPGL02GF2	
10–50 L	NOT REQUIRED		Millipak Gold 40 Unit (0.02 m²) Millipak Gold 60 Unit (0.03 m²) Millipak Gold 100 Unit (0.05 m²)	MPGL04GF2 MPGL06GF3 MPGL1GCF3	
50–300 L	NOT REQUIRED		Opticap XL2 Capsule (0.09 m ²) Millipak Gold 200 Unit (0.1 m ²) Opticap XL4 Capsule (0.19 m ²) OptiSeal Cartridge (0.18 m ²) Opticap XL5 Capsule (0.35 m ²) 5-inch Cartridge (0.35 m ²)	KVGLA02TT3 MPGL2GCF3 KVGLA04TT3 LAGL04TP6 KVGLA05TT1 CVGL75S01	
300–1,500 L	NOT REQUIRED		Opticap XL10 Capsule (0.69 m²) Opticap XL110 Capsule (0.69 m²) 10-inch Cartridge (0.69 m²)	KVGLA10TT1 KVGLA1TTT1 CVGL71TP3	
Solution Concentration > 10 mg/mL					
5–10 L	Milligard SS 0.5 µm + 0.2 µm Pref NOT REQUIRED	ilters	Durapore 0.22 μm Filters Millipak Gold 20 Unit (0.01 m²)	MPGL02GF2	
10–50 L	Opticap XL2 Capsule (0.07 m²)	KWVSSA02TT3	Millipak Gold 40 Unit (0.02 m²) Millipak Gold 60 Unit (0.03 m²) Millipak Gold 100 Unit (0.05 m²)	MPGL04GF2 MPGL06GF3 MPGL1GCF3	
50–300 L	Opticap XL2 Capsule (0.07 m²) Opticap XL4 Capsule (0.16 m²) Opticap XL5 Capsule (0.28 m²) 4-inch Cartridge (0.28 m²)	KWSSA02TT3 KWSSA04TT3 KWSSA05TT1 CWSSM4S03	Opticap XL2 Capsule (0.09 m ²) Millipak Gold 200 Unit (0.11 m ²) Opticap XL4 Capsule (0.19 m ²) Optiseal Cartridge (0.18 m ²) Opticap XL5 Capsule (0.35 m ²) 5-inch Cartridge (0.35 m ²)	KVGLA02TT3 MPGL2GCL3 KVGLA04TT3 LAGL04TP6 KVGLA05TT1 CVGL75S01	
300-1,500 L	Opticap XL10 Capsule (0.7 m²) Opticap XLT10 Capsule (0.7 m²) 10-inch Cartridge (0.7 m²)	KWSSA10TT1 KWSSA10TTT1 CWSS71S03	Opticap XL10 Capsule (0.69 m²) Opticap XLT10 Capsule (0.69 m²) 10-inch Cartridge (0.69 m²)	KVGLA10TT1 KVGLA1TTT1 CVGL71TP3	


Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Large Volume Parenterals (LVP)

Large volume parenterals are single unit doses >100 mL in volume. Typical solutions include water, dextrose (5–50%), amino acids, salts and viscous Total Parenteral Nutrition (TPN) components with batch sizes in the tens of thousands of liters. Filtration is used for particle and colloid removal as well as bioburden reduction.

For details on Tank Venting 4, see page 70.

Typical Process Flow



Understanding the **Options**

Essential Process Requirements	Recommended Filter	Filter Characteristics
Prefiltration		
 Remove colloidal and particulate contaminants Preserve product purity Operate consistently at high differential pressures and flow rates Prevent plugging and extend the life of downstream filters Able to withstand demanding sanitization cycles Run efficiently to ensure process economics Solute concentration impacts filter selection 	Double-layer Milligard Filters (Grade SS, 0.5 μm + 0.2 μm, or Grade SC, 1.2 μm + 0.5 μm)	 Double-layer pleated configuration of mixed esters of cellulose membranes remove particles and colloids High porosity membranes operate at high flow rates and low pressure drops Better suited for low-solute concentrations Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Robust construction validated to withstand multiple SIP or hot water sanitization cycles Available in a variety of pore sizes to accommodate the needs of each user. Grade SS is commonly used to protect downstream 0.22 µm sterilizing-grade filters. Grade SC is better suited to protect 0.45 µm membrane filters. Choice should be made based on small-scale testing.
	Double-layer Polysep II Filters (Grade W6, 1 µm+ 0.5 µm, or Grade W3, 1 µm + 0.2 µm)	 Borosilicate glass top layer enhances particle and loading capacity in high solute applications Mixed esters of cellulose membrane bottom layer ensures high retention and filtrate quality Ideal for high solute concentration such as 5% Dextrose Robust construction validated to withstand multiple SIP or hot water sanitization cycles Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Available in a variety of pore sizes to accommodate the needs of each user. Grade W3 is commonly used to protect downstream 0.22 µm membrane filters. Grade W6 is better suited to protect 0.45 µm membrane filters. Choice should be made based on small-scale testing.

Essential Process Requirements	Recommended Filter	Filter Characteristics
Bioburden Reduction		
 Reduce bioburden prior to terminal sterilization Preserve product purity Operate consistently at high flow rates Able to withstand demanding sanitization requirements 	 Double-layer Durapore 0.45 µm Filters (with 0.5 µm prefilter layer) 	 Low protein-binding PVDF membrane with prefilter Retentive membrane reduces bioburden Low extractables and non-fiber releasing PVDF chemistry preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity tested to ensure quality Validated for multiple SIP and hot water sanitization cycles
	2 Durapore CBR 0.2 μm Filters	 Low protein-binding 0.2 µm PVDF membrane Bacterial retentive membrane reduces bioburden Low extractables and non-fiber releasing PVDF chemistry preserve product purity and yield High flow rate at low pressure drop for reliable economic processing 100% integrity tested to ensure quality Validated for multiple SIP and hot water sanitization cycles
Final Sterile Filtration		
 Final Sterile Filtration Sterile filtration prior to terminal sterilization Operate consistently at high differential pressures and flow rates Able to withstand rigorous sanitization and process requirements Ensure product safety 	3 Durapore 0.22 µm Filters	 Sterilizing-grade PVDF membrane 100% Integrity testing and thousands of existing applications assure proven performance Although 0.22 µm membrane is typical for this application, Durapore filters are available in several pore sizes and in single-layer or multilayer configurations to accommodate the needs of each user, the degree of protection required for the downstream process and the plugging characteristics of the fluid. Choice should be based on small-scale testing. Integrity testable on-site
	ALTERNATIVE: If a PES membrane is requ	iired, Millipore suggests including Millipore's Express SHF Filters in your screening trials.





Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
OptiScale Capsules Double-layer Milligard SC 1.2 µm + 0.5 µm membrane Double-layer Milligard SS 0.5 µm + 0.2 µm membrane Double-layer Polysep II W6 1.0 µm + 0.2 µm membrane Double-layer Polysep II W3 1.0 µm + 0.2 µm membrane Durapore 0.45 µm membrane (order with 0.5 µm prefilter SW06A47FF3) Durapore CBR 0.2 µm membrane Single-layer Durapore 0.22 µm membrane Single-layer Millipore Express SHF membrane	13.8 cm ²	SWSCA47FF3 SWSSA47FF3 SGW6A47FF3 SGW3A47FF3 SVGLA47FF3 SVGLA47FF3 SVGLA47FF3 SGEPA47FF3

Recommended Filters

Prefiltration and Bioburden Reduction used in combination.

Low Solute Concentration (e.g. 5% Dextrose)

	Area/Filter	Catalogue No.		Area/Filter	Catalogue No.
Milligard SS (0.5 µm + 0.2 µm) Filters			Durapore CBR 0.2 µm Filters		
Opticap XL10 Capsule	0.7 m ²	KWSSA10TT1	10-inch Cartridge	0.69 m ²	CVDI71TPS
Opticap XLT10 Capsule	0.7 m ²	KWSSA1TTT1	20-inch Cartridge	1.4 m ²	CVDI72TPS
10-inch Cartridge	0.7 m ²	CWSS71S03	30-inch Cartridge	2.1 m ²	CVDI73TPS
Opticap XLT20 Capsule	1.4 m ²	KWSSA2TTT1	40-inch Cartridge	2.8 m ²	CVDI74TPS
20-inch Cartridge	1.4 m ²	CWSS72S03	Ŭ		
Opticap XLT30 Capsule	2.1 m ²	KWSSA3TTT1			
30-inch Cartridge	2.1 m ²	CWSS73S03			
40-inch Cartridge	2.8 m^2	CWSS74S03			
Milligard SC (1.2 µm + 0.5 µm) Filters			Durapore 0.45 µm Filters + 0.5 µm Pre	efilter Layer	
Opticap XL10 Capsule	0.7 m ²	KWSCA10TT1	Opticap XL10 Capsule	0.69 m ²	KVHLA10TT1
Opticap XLT10 Capsule	0.7 m ²	KWSCA1TTT1	10-inch Cartridge	0.69 m ²	CVHL71TP3
10-inch Cartridge	0.7 m ²	CWSC71S03	20-inch Cartridge	1.4 m ²	CVHL72TP3
Opticap XLT20 Capsule	1.4 m ²	KWSCA2TTT1	30-inch Cartridge	2.1 m ²	CVHL73TP3
20-inch Cartridge	1.4 m ²	CWSC72S03	40-inch Cartridge	2.8 m ²	CVHL74TP3
Opticap XLT30 Capsule	2.1 m ²	KWSCA3TTT1	Ŭ		
30-inch Cartridge	2.1 m ²	CWSC73S03			
40-inch Cartridge	2.8 m^2	CWSC74S03			

Prefiltration and Bioburden Reduction used in combination.

High Solute Concentration (e.g. up to 50% Dextrose) Area/Filter Catalogue No. Area/Filter Catalogue No. Polysep II W3 (1.0 µm + 0.2 µm) Filters Durapore CBR 0.2 µm Filters 0.69 m^2 Opticap XL10 Capsule $0.46 \ \text{m}^2$ KGW3A10TT1 10-inch Cartridge CVDI71TPS Opticap XLT10 Capsule 10-inch Cartridge 0.46 m² KGW3A1TTT1 20-inch Cartridge 1.4 m² CVDI72TPS CGW371S03 0.46 m² 30-inch Cartridge 2.1 m² CVDI73TPS Opticap XLT20 Capsule 0.92 m^2 KGW3A2TTT1 40-inch Cartridge $2.8 \ m^2$ CVDI74TPS 20-inch Cartridge 0.92 m² CGW372S03 Opticap XLT30 Capsule $1.38 \ \text{m}^2$ KGW3A3TTT1 30-inch Cartridge 1.38 m^2 CGW373S03 40-inch Cartridge CGW374S03 1.84 m^2 Polysep II W6 (1.0 µm + 0.5 µm) Filters Durapore 0.45 µm Filters + 0.5 µm Prefilter Layer Opticap XL10 Capsule KGW6A10TT1 Opticap XL10 Capsule 0.69 m² 0.46 m^2 KVHLA10TT1 Opticap XLT10 Capsule 10-inch Cartridge $0.69 \ \text{m}^2$ CVHL71TP3 $0.46 \ \text{m}^2$ KGW6A1TTT1 10-inch Cartridge 0.46 m² CGW671S03 20-inch Cartridge 1.4 m^2 CVHL72TP3 0.92 m² Opticap XLT20 Capsule KGW6A2TTT1 30-inch Cartridge 2.1 m² CVHL73TP3 20-inch Cartridge $0.92 \ \text{m}^2$ CGW672S03 40-inch Cartridge CVHL74TP3 $2.8 \ \text{m}^2$ Opticap XLT30 Capsule 1.38 m² KGW6A3TTT1 CGW673S03 30-inch Cartridge 1.38 m^2 CGW674S03 40-inch Cartridge 1.84 m^2

Final Sterile Filtration	Area/Filter	Catalogue No.
Durapore 0.22 µm Filters		
Opticap XL10 Capsule	0.69 m ²	KVGLA10TT1
Opticap XLT10 Capsule	0.69 m ²	KVGLA1TTT1
Opticap XL10 Gamma-compatible Capsule	0.69 m ²	KVGLG10TT1
XLT10 Gamma-compatible Capsule	0.69 m ²	KVGLG1TTT1
10-inch Cartridge	0.69 m ²	CVGL71TP3
Opticap XLT20 Capsule	1.4 m ²	KVGLA2TTT1
XLT20 Gamma-compatible Capsule	1.4 m ²	KVGLG2TTT1
20-inch Cartridge	1.4 m ²	CVGL72TP3
Opticap XLT30 Capsule	2.1 m ²	KVGLA3TTT1
XLT30 Gamma-compatible Capsule	2.1 m ²	KVGLG3TTT1
30-inch Cartridge	2.1 m ²	CVGL73TP3
40-inch Cartridge	2.8 m ²	CVGL74TP3

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Ophthalmic Solutions

Ophthalmic solutions range from contact lens cleaning and storage solutions to eye surgery and treatment products. These preparations must meet stringent regulatory requirements and product specifications. Though the major component in

ophthalmics is water, many contain salts

such as NaCl, preservatives, petrolatum for ointments and thixotropic polymeric substances for lubricating agents. Heat-labile components are processed via sterile filtration for particle and bioburden reduction and microorganism removal.

For details on Tank Venting (3), see page 70.

Typical **Process Flow**










Vent 3



Understanding the **Options**

Essential Process Requirements	Recommended Filter	Filter Characteristics
Prefiltration		
 Reduce particles and bioburden Extend the life of final filters Must be robust for high volume processes Run efficiently for optimal process economics 	Double-layer Polysep II Filters (Grade W6, 1 μm + 0.5 μm)	 Borosilicate glass top layer enhances particle and loading capacity in high solute applications Mixed esters of cellulose membrane bottom layer ensures high retention and filtrate quality Robust construction validated to withstand multiple SIP or hot water sanitization cycles Non-fiber releasing structure preserves product purity 100% integrity tested to ensure quality Available in a variety of pore sizes to accommodate the needs of each user. Grade W6 is commonly used in this application. Choice should be made based on small-scale testing.
Sterile Filtration		
 Sterilizing-grade filter to remove microorganisms Operate consistently at high flow rates Must be robust for high volume processes Run efficiently to ensure process economics 	2 Charged Durapore 0.22 µm Filters	 Sterilizing-grade PVDF membrane Ideal solution when preservative binding is a concern High flow rates and throughput, low extractables and protein binding 100% Integrity testing to ensure performance
CONTRACT	2 Millipore Express SHF 0.2 µm Filters	 Sterilizing-grade PES membrane providing broad chemical compatibility across a wide pH range (1–14) Asymmetric pore structure delivers extremely high flow rates at low preservative binding 100% integrity tested to ensure quality



Process Development Screening

Millipore recommends running small-scale trials for capacity and throughput screening. This table provides details on process development devices for recommended filters and alternatives since the ideal solution will vary based on each fluid stream. The following order table is for recommended devices only.

Filter Format	Area/Filter	Catalogue No.
OptiScale Capsules Polysep II W6 1.0 µm + 0.5 µm membrane Millipore Express SHF membrane	13.8 cm ²	SGW6A47FF3 SGEPA47FF3
Charged Durapore 0.22 µm, 47 mm filter discs	13.8 cm ²	CCGL04725


Recommended Filters

	Small-Scale Processing	<100 L	Large-Scale Processing >100 L		
Media/Membrane	Device (area/filter)	Catalogue No.	Device (area/filter)	Catalogue No.	
Prefiltration					
Double-layer Polysep II Filters (Grade W6, 1.0 µm + 0.5 µm)	Opticap XL2 Capsule (0.06 m ²) Opticap XL4 Capsule (0.11 m ²) Opticap XL5 Capsule (0.19 m ²) 4-inch Cartridge (0.19 m ²)	KGW6M02TT3 KGW6A04TT3 KGW6A05TT1 CGW674S03	Opticap XL10 Capsule (0.46 m ²) Opticap XL110 Capsule (0.46 m ²) 10-inch Cartridge (0.46 m ²) Opticap XLT20 Capsule (0.92 m ²) 20-inch Cartridge (0.92 m ²) Opticap XLT30 Capsule (1.38 m ²) 30-inch Cartridge (1.38 m ²)	KGW6A10TT1 KGW6A1TTT1 CGW671S03 KGW6A2TTT1 CGW672S03 KGW6A3TTT1 CGW673S03	
Sterilizing-grade Filtration					
Charged Durapore 0.22 µm PVDF Filters	Optiseal Cartridge (0.18 m ²)	LCGL04TP6	10-inch Cartridge (0.69 m²) 20-inch Cartridge (1.4 m²) 30-inch Cartridge (2.1 m²)	CCGL71TP1 CCGL72TP1 CCGL73TP1	
Millipore Express SHF 0.2 µm PES Filters	Opticap XL3 Capsule (0.16 m²) Opticap XL5 Capsule (0.29 m²) 5-inch Cartridge (0.29 m²)	KGEPA03TT3 KGEPA05TT1 CGEP75TP3	Opticap XL10 Capsule (0.54 m ²) Opticap XL110 Capsule (0.54 m ²) 10-inch Cartridge (0.54 m ²) Opticap XLT20 Capsule (1.08 m ²) 20-inch Cartridge (1.08 m ²) Opticap XLT30 Capsule (1.62 m ²) 30-inch Cartridge (1.62 m ²)	KGEPA10TT1 KGEPA1TTT1 CGEP71TP3 KGEPA2TTT1 CGEP72TP3 KGEPA3TTT1 CGEP73TP3	

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

Facilities Water

Pharmaceutical grade water is defined as feed water common to process systems such as washers, autoclaves or secondary water purification systems such as VVFI distillation. Filters in central water systems may be exposed to a variety of contaminants. The filter train should reduce the bioburden and contaminant load while maintaining a low pressure drop for extended periods of time. Filters in DI systems must maintain low pressure drops throughout long throughput cycles and may be exposed to particle loads for resin beds.





Recommended Filters

Flowrate (Lpm)	Prefiltration	Bioburden Reduction	Endotoxin Removal	Sterilizing Filtration
	Clarigard 3.0 µm Filters	Durapore CBR 0.2 µm Filters	Charged Durapore 0.22 µm Filters	Millipore Express SHF 0.2 µm Filters
1–15	10-inch Cartridge: D03071S01	10-inch Cartridge: CVDI71TPS	10-inch Cartridge: CCGL71TP1	10-inch Cartridge: CGEP71TP3
15-30	20-inch Cartridge: D03072S01	20-inch Cartridge: CVDI72TPS	20-inch Cartridge: CCGL72TP1	20-inch Cartridge: CGEP72TP3
30–45	20-inch Cartridge: D03072S01	20-inch Cartridge: CVDI72TPS	30-inch Cartridge: CCGL73TP1	30-inch Cartridge: CGEP73TP3
Per 45	30-inch Cartridge: D03073S01	30-inch Cartridge: CVDI73TPS	30-inch Cartridge: CCGL73TP1	30-inch Cartridge: CGEP73TP3

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

For details on Millipore's lab water systems visit www.millipore.com/H2O

LENNTECH

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Tank Venting and Air Filtration

Hydrophobic sterilizing-grade filters are commonly used as air vents on processing tanks. The goal of the application is to maintain near ambient pressure in the tank while ensuring sterility in the tank. The tank vent filter removes viruses and microorganisms from the gas as it flows in or out of the tank.

Filter requirements

- Sterilizing-grade PTFE membrane
- Integrity testable, bacteria and virus retentive
- Robust construction validated for multiple SIP cycles
- Delivers high flow rates
- 100% integrity tested to ensure quality

Typical **Process Flow**

Vent Filter

Sizing Your Vent Filter

Air flows in and out of a process tank for two reasons. The first is to replace a volume of liquid as it is pumped in or out of the tank. Sizing the tank vent filter for pump-out or fill rate is relatively simple. The air flow rate will be equal to the pump-out or fill rate. With flow rate and pressure determined, a flow/ ΔP curve can be used to determine sizing.

The second reason air will flow into a process tank is to compensate for the volume change associated with steam condensation. At the end of a tank steamin-place procedure, steam in the tank will cool and undergo a phase change to liquid water. There is over 1,000X difference in volume between an amount of water in gas phase vs. liquid phase. During cooling, sterilized ambient air must be allowed into the tank to prevent vacuum. Sizing the vent filter for steam collapse requires knowing the vacuum rating of the tank and the convective cooling rate. These can be calculated based on the tank dimensions including height, diameter and wall thickness. Millipore has developed a computer program to facilitate these calculations.

Improper tank vent sizing can result in low pump-out rates, loss of sterility due to rupture disk or filter failure, or worst case, tank implosion. Fortunately, proper sizing is not difficult as long as the flow requirements and driving force are understood.



Recommended Filters

Filter Format	Area/Filter	Catalogue No.
Aervent Hydrophobic Filters		
Aervent-50 capsule	19.6 m ²	MTGR15010
Opticap XL2 capsule	0.10 m ²	KTGRA02TT3
Optiseal cartridge	0.18 m ²	LAGR04TP6
Opticap XL4 capsule	0.21 m ²	KTGRA04TT3
Opticap XL5 capsule	0.32 m ²	KTGRA05TT1
5-inch cartridge	0.32 m ²	CTGR75S01
Opticap XL10 capsule	0.65 m ²	KTGRA10TT1
10-inch cartridge	0.65 m ²	CTGR71TP1
20-inch cartridge	1.3 m ²	CTGR72TP1
30-inch cartridge	1.95 m ²	CTGR73TP1

Filters are available in many sizes, configurations and formats. See the quick reference tables on page 2 for a detailed list.

The following are registered marks of Millipore Corporation.

Access[®] Services Aervent® Filters Biomax[®] Membrane Clarigard[®] Filters Durapore® Membrane and Filters Lynx[®] Connectors Milligard[®] Filters Millipak® Units Millipore Express® Membrane Millipore[®] Millistak+® Filters Opticap[®] Capsules OptiScale® Capsules Optiseal[®] Filters Pellicon® Cassettes Polygard[®] Filters Prosep® Media Ultracel® Membrane Viresolve® Filters

The following are trademarks of Millipore Corporation.

Mobius[™] Solutions Polysep[™] II Filters Prostak[™] Modules

HyClone and HyQ are registered trademarks, and BioProcess Container (BPC). Mixtainer and Smartainer are trademarks of HyClone Laboratories, Inc.

C-Flex is a registered trademark of Consolidated Polymer Technologies Inc.

Colder Products is a registered trademark of Colder Products Corporation.

ISO is a registered trademark of the International Organization for Standardization or an affiliated company.

Ordering Information

Lenntech

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289



LENNTECH

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Copyright 2004 Millipore Corporation, Billerica, MA 01821 U.S.A. All rights reserved. Lit. No. SG1500EN00 Rev. A Printed in U.S.A. 12/04 04-204 Photography, Robert Fraher.

MILLIPORE